

Water-based Fluoropolymer Coating NEOFLON PFA AD-2CRER

 TECHNICAL
DATASHEET

Water-based PFA topcoat for non-stick property.

Introduction

- NEOFLON PFA AD-2 grade is a water-based PFA topcoat.
- NEOFLON PFA AD-2CRER makes a clear topcoat layer displaying non-stick property.
- It makes a pinhole-free film.

Characteristics

Film appearance	Viscosity [cP]	pH	Solid content [mass%]
Clear	220	9	50

Physical properties of the coating film

Items	Unit	Data	Method of measurement ※
Pencil hardness (25°C)		H – 3H	JIS K6894 (Stripping hardness of base material)
Cross-cut adhesion		100/100	JIS K5400 8.5 (Stripping with cellophane tape, 10 times)
Contact angle (Water) (Hexadecane)	degree	110 – 116 50 – 56	Contact angle meter at 25°C

※ The coating film was evaluated with a test piece below.

Substrate: Aluminum plate roughened with Tosa Emely Extra #80/#100=50/50

Primer: EK-1909S21R, approximately 10µm thick

Topcoat: Approximately 10~15µm thick

* The numeric values above are typical and not guaranteed.

Handling method/Safety information

- Be sure to read the notes on SDS and labels before use.
- This product is intended for general industry, and therefore its adequacy and safety as a raw material for medical purposes cannot be guaranteed.

For more information, visit our website.

DAIKIN INDUSTRIES, LTD.

<https://www.daikinchemicals.com/>

tds-ad-2crer-E_ver01_Mar_2018

Copyright (C) DAIKIN INDUSTRIES, LTD., 2018