

# Fluoropolymer NEOFLON FEP NF-0125

 TECHNICAL  
DATASHEET

**NEOFLON FEP NF - 0125 is a highly transparent fluoropolymer film with characteristics close to PTFE.**

## Introduction

- NEOFLON FEP film is smooth high-performing non-stretch film which is formed by melt extrusion with NEOFLON FEP material.
- NEOFLON FEP film consists of atoms of carbon and fluorine, and has outstanding heat and chemical resistance, non-adhesion, and non-flammability.
- It also possesses fabricating characteristics, including heat sealing, thermoforming, welding and heat bonding as well as adhesion (surface treatment items).

## General characteristics

Items	Unit	Figures	Test method
Average thickness	μm	125	ASTM D 3368
Melting point	°C	270	DSC method
Tensile strength	MPa	53.0	ASTM D3368
Elongation	%	390	ASTM D3368
Heat shrinkage rate (MD/TD)	%	-1.6 / -0.1	ASTM D3368 200°C×10min

\* The figures in this table are typical measured values at our company, not the values for guaranteeing.

## Handling / Safety information

- Be sure to read the notes on SDS and labels before use.
- This product is intended for general industry, and therefore its adequacy and safety as a raw material for medical purposes cannot be guaranteed.

## Packaging

- The product is rolled on a paper core, hung with a protector at both ends, and packed in a carton box.

For more information, visit our website.

**DAIKIN INDUSTRIES, LTD.**

<https://www.daikinchemicals.com/>

tds-nf-0125-E\_ver02\_May\_2019  
Copyright (C) DAIKIN INDUSTRIES, LTD., 2018