

# **Fluoropolymer NEOFLON PFA AP-230**

**TECHNICAL DATASHEET** 

### NEOFLON PFA AP-230 is a fluororesin that is excellent in melt flowability. It is suitable for extrusion molding.

#### Introduction

- **AP-230** is a copolymer of tetrafluoroethylene and perfluoroalkyl vinyl ether.
- Good melt flowability while maintaining excellent properties of PTFE. It can be melt-molded as a thermoplastic resin by extrusion molding, transfer molding, compression molding and the like.
- It has been used for tubes, pipes, sheets, lining applications.
- It is widely used as a **thick plate** material by compression molding.
- Excellent chemical resistance which is not affected by most of the chemicals.
- It retains flexibility without losing toughness under the environment from cryogenic to high temperature.
- Excellent heat resistance. Continuous use temperature is 260 °C.
- Low dielectric constant and dielectric loss tangent in a wide range of temperature and frequency.
- It shows high electrical resistance and dielectric strength.
- Nonflammable like POLYFLON PTFE and NEOFLON FEP.
- Excellent weather resistance. No properties change even when exposed outside for a long time.
- Non-stickiness. It shows excellent releasability and water repellency / oil repellency.

#### **General physical properties**

Item	Unit	Value	Test Method
MFR	g/10min	2.0	ASTM D 3307 Compliant
Melting Point	°C	307	DSC
Specific Gravity	-	2.14	ASTM D 792 Compliant
Tensile Strength	MPa	35	ASTM D 1708 Compliant
Elongation	%	380	ASTM D 1708 Compliant

<sup>\*</sup> The above values are representative values, not guaranteed values.

#### Handling method / Safety information

- Be sure to read the notes on SDS and labels before use.
- This product is intended for general industry, and therefore its adequacy and safety as a raw material for medical purposes cannot be guaranteed.





### **Packing specification**

25Kg

For more information, visit our website.

## DAIKIN INDUSTRIES,LTD.

https://www.daikinchemicals.com/

tds-ap-230-E\_ver02\_May\_2019 Copyright (C) DAIKIN INDUSTRIES, LTD., 2018