

Printing date 16.03.2023

Version number 1

Revision: 16.03.2023

**\* SECTION 1: Identification of the substance/mixture and of the company/undertaking****1.1 Product identifier****Trade name:** DAI-EL LATEX GLP-103SR**Synonyms:**

UNIDYNE TG-8111 (B)

UNIDYNE TG-5506 (B)

**Article number:** GLP103SR STD**1.2 Relevant identified uses of the substance or mixture and uses advised against:****Sector of Use** SU8 Manufacture of bulk, large scale chemicals (including petroleum products)**1.3 Details of the supplier of the safety data sheet****Manufacturer/Supplier:**

DAIKIN INDUSTRIES, LTD. CHEMICALS DIVISION:

OSAKA UMEDA TWIN TOWERS SOUTH, 1-13-1 Umeda, Kita-ku, Osaka-shi, Osaka, 530-0001, Japan

Phone: +81-6-6147-9702 Fax: +81-6-6147-9807

**Further information obtainable from:**<http://www.daikin.com/>[sales@daikinchem.de](mailto:sales@daikinchem.de)**1.4 Emergency telephone number:**

Japan: +81-6-6349-7521

China: +86-532-8388-9090, +86-21-34151689

South Korea: +82-2-568-1722

Americas: CHEMTREC +1-800-424-9300 (Outside US/Canada: +1-703-527-3887)

Europe: +49-211-179 225-0

**\* SECTION 2: Hazard identification****2.1 Classification of the substance or mixture****Classification according to Regulation (EC) No 1272/2008**

Flam. Liq. 2 H225 Highly flammable liquid and vapour.



Repr. 2 H361d Suspected of damaging the unborn child.

STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.



Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2 H319 Causes serious eye irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

**2.2 Label elements****Labelling according to Regulation (EC) No 1272/2008:**

The product is classified and labelled according to the CLP regulation.

**Signal word:** Danger**Hazard-determining components of labelling:**

Toluene

Isopropyl alcohol

**Precautionary statements:**

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Printing date 16.03.2023

Version number 1

Revision: 16.03.2023

Trade name: **DAI-EL LATEX GLP-103SR**

- P241 Use explosion-proof [electrical/ventilating/lighting] equipment.  
P303+P361+P353 **IF ON SKIN (or hair):** Take off immediately all contaminated clothing. Rinse skin with water [or shower].  
P305+P351+P338 **IF IN EYES:** Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P405 Store locked up.  
P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

### **SECTION 3: Composition/information on ingredients**

#### **Information on ingredients:**

Acryl resin	1 – 10%
Silane coupling agent	1 – 10%
CAS: 108-88-3 Toluene	35-45%
Flam. Liq. 2, H225 Repr. 2, H361d; STOT RE 2, H373; Asp. Tox. 1, H304 Skin Irrit. 2, H315; STOT SE 3, H336	
CAS: 67-63-0 Isopropyl alcohol	35-45%
Flam. Liq. 2, H225 Eye Irrit. 2, H319; STOT SE 3, H336	

**Additional information:** For the wording of the listed hazard phrases refer to section 16.

### **SECTION 4: First aid measures**

#### **4.1 Description of first aid measures**

**General information:** Seek medical treatment.

**After inhalation:** Supply fresh air; consult doctor in case of complaints.

**After skin contact:**

Remove contaminated clothes immediately.

Immediately wash with water and soap and rinse thoroughly.

Consult a doctor in case of complaints.

**After eye contact:**

Immediately rinse with a lot of water for several minutes. Remove contact lenses if possible. Continue rinsing.

Consult an ophthalmologist in case of complaints.

**After swallowing:**

Rinse mouth with water. Do not induce vomiting.

Consult a doctor in case of complaints.

**4.2 Most important symptoms and effects, both acute and chronic:** No further relevant information available.

**4.3 Indication of any immediate medical attention and special treatment needed:**

No further relevant information available.

### **SECTION 5: Firefighting measures**

#### **5.1 Extinguishing media**

**Suitable extinguishing agents:**

Foam

Fire-extinguishing powder

CO<sub>2</sub>

**For safety reasons unsuitable extinguishing agents:** Water with full jet

#### **5.2 Special hazards arising from the substance or mixture:**

Formation of toxic gases is possible during heating or in case of fire.

Receptacle may explode when heated.

Extremely flammable; can ignite easily with heat, sparks, fire.

#### **5.3 Advice for firefighters:**

The flash point is extremely low: water spray can be used for a large fire only if other extinguishing means have no effect.

Printing date 16.03.2023

Version number 1

Revision: 16.03.2023

**Trade name: DAI-EL LATEX GLP-103SR**

Remove receptacles from area of fire if possible.

**Protective equipment:**

Wear self-contained breathing apparatus and protective suit.

Do not inhale explosion gases or combustion gases.

**SECTION 6: Accidental release measures****6.1 Personal precautions, protective equipment and emergency procedures:**

Ensure adequate ventilation before entering the area.

Stay on the windward side.

Keep out unauthorized persons.

Wear appropriate protective devices (See Section 8 Exposure Controls/Personal Protection).

Avoid contact with eyes and skin.

Do not swallow the product.

**6.2 Environmental precautions:** Prevent seepage into sewage system, workpits and cellars.

**6.3 Methods and material for containment and cleaning up:**

Do not flush with water or aqueous cleansing agents

For a small amount of leakage: Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders) or collect in an empty container that can be sealed tightly.

For a small amount of leakage: Use clean anti-static tools when absorbing the product.

For a large amount of leakage: Enclose with banks to avoid outflow. Lead the leakage to a safe place and collect.

Remove ignition sources immediately.

Ground all equipment when the product leaks.

There is a danger of explosion. Prepare fire extinguisher in case of emergency.

**6.4 Reference to other sections:**

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

**\* SECTION 7: Handling and storage****7.1 Precautions for safe handling:**

Open and handle receptacle with care.

Ensure good ventilation/exhaustion at the workplace.

Handle with care. Avoid jolting, friction and impact.

Do not handle until all safety precautions have been read and understood.

**Information about fire - and explosion protection:**

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Use flame proof electric/lighting devices and ventilation equipment.

Ground/bond container and receiving equipment.

**7.2 Conditions for safe storage, including any incompatibilities:****Storage****Requirements to be met by storerooms and receptacles:**

Store in a cool and dry location.

Provide solvent resistant, sealed floor.

Prevent any seepage into the ground.

Keep containers tightly sealed.

**Information about storage in one common storage facility:**

See section 10 for information on incompatible materials.

**Further information about storage conditions:**

Protect from heat and direct sunlight.

Store containers in a well ventilated area.

Store locked up.

**7.3 Specific end use(s):** No further relevant information available.

**\* SECTION 8: Exposure controls/personal protection**

**8.1 Control parameters** No further information available.

Printing date 16.03.2023

Version number 1

Revision: 16.03.2023

Trade name: DAI-EL LATEX GLP-103SR

**Ingredients with limit values that require monitoring at the workplace:****CAS: 108-88-3 Toluene**IOELV (EU) Short-term value: 384 mg/m<sup>3</sup>, 100 ppmLong-term value: 192 mg/m<sup>3</sup>, 50 ppm

Skin

**8.2 Exposure controls****Appropriate engineering controls** No further data; see item 7.**Individual protection measures, such as personal protective equipment****General protective and hygienic measures:**

Wash hands before breaks and at the end of work.

Do not eat or drink while working.

Keep away from tobacco products.

**Respiratory protection:**

Use respiratory protective device with filters for organic and acid gas (or airline respirators in some cases) if formation of toxic gases is possible while the product is heated.

Use respiratory protective device with organic gas cartridge.

**Hand protection**

Protective gloves

**Material of gloves:** Rubber**Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

**Eye/face protection**

Safety glasses

**Body protection:** Protective work clothing**\* SECTION 9: Physical and chemical properties****9.1 Information on basic physical and chemical properties****General Information****Physical state**

Fluid

**Colour:**

Transparent

**Odour:**

Alcohol-like

**Odour threshold:**

Not determined.

**Melting point/freezing point:**

Undetermined.

**Boiling point or initial boiling point and boiling range**

Undetermined.

**Flammability**

Highly flammable.

**Lower and upper explosion limit****Lower explosive limit:**

1.2 Vol %

**Upper explosive limit:**

12 Vol %

**Flash point:**

5 °C (SCC)

**Decomposition temperature:**

No further information available.

**pH**

Not determined.

Not determined.

**Viscosity:****Kinematic viscosity**

Not determined.

**Dynamic:**

Not determined.

Printing date 16.03.2023

Version number 1

Revision: 16.03.2023

Trade name: DAI-EL LATEX GLP-103SR

**Solubility****water:**

No further information available.

Not determined.

**Partition coefficient n-octanol/water (log value)**

No further information available.

Not determined.

**Vapour pressure:**

No further information available.

**Density and/or relative density****Density at 20 °C:**0.85 g/cm<sup>3</sup>**Relative density**

Not determined.

**Vapour density**

Not determined.

**Particle characteristics**

No further information available.

**9.2 Other information:****Form:**

Liquid

**Auto-ignition temperature:**

Product is not self-igniting.

**Explosive properties:**

Product is not explosive. However, formation of explosive air/vapour mixtures are possible.

**Evaporation rate**

Not determined.

**Information with regard to physical hazard classes****Explosives**

Not applicable

**Flammable gases**

Not applicable

**Aerosols**

Not applicable

**Oxidising gases**

Not applicable

**Gases under pressure**

Not applicable

**Flammable liquids**

Highly flammable liquid and vapour.

**Flammable solids**

Not applicable

**Self-reactive substances and mixtures**

Not applicable

**Pyrophoric liquids**

Not applicable

**Pyrophoric solids**

Not applicable

**Self-heating substances and mixtures**

Not applicable

**Substances and mixtures, which emit flammable gases****in contact with water**

Not applicable

**Oxidising liquids**

Not applicable

**Oxidising solids**

Not applicable

**Organic peroxides**

Not applicable

**Corrosive to metals**

Not applicable

**Desensitised explosives**

Not applicable

**SECTION 10: Stability and reactivity****10.1 Reactivity** No further relevant information available.**10.2 Chemical stability****Thermal decomposition / conditions to be avoided:** To avoid thermal decomposition do not overheat.**10.3 Possibility of hazardous reactions:** No dangerous reactions known under normal conditions of use.**10.4 Conditions to avoid:** Keep away from heat, sparks, flame, high temperature.**10.5 Incompatible materials:** Oxidizing agents**10.6 Hazardous decomposition products:**

Carbon monoxide

Carbon dioxide

As for decomposition products, particulate matters and extremely toxic/corrosive fumes may be generated (HF, carbonyl fluoride, monomers, perfluoroisobutylene).

Decomposition products differ depending on the temperature and conditions.

**\* SECTION 11: Toxicological information****11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008****Acute toxicity** Based on available data, the classification criteria are not met.

Printing date 16.03.2023

Version number 1

Revision: 16.03.2023

**Trade name: DAI-EL LATEX GLP-103SR****LD/LC50 values relevant for classification:****CAS: 108-88-3 Toluene**

Oral LD50 5000 mg/kg (Rat)

Dermal LD50 12124 mg/kg (Rabbit)

Inhalative LC50/4h 5320 ppm (Mouse)

**Skin corrosion/irritation:** Causes skin irritation.**Serious eye damage/irritation:** Causes serious eye irritation.**Respiratory or skin sensitisation:** No further information available.**Reproductive toxicity:** Suspected of damaging the unborn child.**STOT-single exposure:** May cause drowsiness or dizziness.**STOT-repeated exposure:** May cause damage to organs through prolonged or repeated exposure.**Aspiration hazard:** May be fatal if swallowed and enters airways.**Other information (about experimental toxicology):** No further information available.**Subacute to chronic toxicity:** No further information available.**Additional toxicological information:**

General effects:

Fumes generated during burning may cause "polymer fume fever" (flu-like symptoms such as fever, chill, cough). This may last for a whole day and night.

Fumes are not absorbed in skin. No sensitizing effect known.

Effects of hydrogen fluoride:

Low concentration of hydrogen fluoride may cause feeling of dyspnea, cough, irritation in eyes, nose, throat, fever, chill for 1-2 days.

After that, dyspnea, cyanosis and pulmonary edema may be seen.

High concentration of hydrogen fluoride damages liver and kidney.

Effects of carbonyl fluoride:

Skin: Irritation or eruption

Eye: Ulcer in cornea, conjunctiva

Respiratory system: Irritation

Lung: Temporary symptoms such as cough, pain, dyspnea

Persons who have experienced lung diseases are vulnerable to toxicity caused by excessive exposure to pyrolysis products

**11.2 Information on other hazards:****Endocrine disrupting properties:**

None of the ingredients is listed.

**\* SECTION 12: Ecological information****12.1 Toxicity****Aquatic toxicity:** No further relevant information available.**12.2 Persistence and degradability:** No further relevant information available.**12.3 Bioaccumulative potential:** No further relevant information available.**12.4 Mobility in soil:** No further relevant information available.**12.5 Results of PBT and vPvB assessment****PBT:** No further relevant information available.**vPvB:** No further information available.**12.6 Endocrine disrupting properties**

The product does not contain substances with endocrine disrupting properties.

For information on endocrine disrupting properties see section 11.

**12.7 Other adverse effects:****Ecotoxicological effects:** no data**SECTION 13: Disposal considerations****13.1 Waste treatment methods****Recommendation:** Disposal must be made according to official regulations.



Printing date 16.03.2023

Version number 1

Revision: 16.03.2023

Trade name: DAI-EL LATEX GLP-103SR

**Uncleaned packaging****Recommendation:** Disposal must be made according to official regulations.**\* SECTION 14: Transport information****14.1 UN number or ID number****ADR, IMDG, IATA** UNI263**14.2 UN proper shipping name:****ADR, IMDG, IATA** PAINT**14.3 Transport hazard class(es):****ADR****Class:** 3 (F1) Flammable liquids.**Label:** 3**IMDG, IATA****Class:** 3 Flammable liquids.**Label:** 3**14.4 Packing group:****ADR, IMDG, IATA** II**14.5 Environmental hazards:****Marine pollutant:** No**14.6 Special precautions for user:** Warning: Flammable liquids.**Hazard identification number (Kemler code):** 33**EMS Number:** F-E,S-E**Stowage Category** B**14.7 Maritime transport in bulk according to IMO instruments**

Not applicable.

**Transport/Additional information:** Avoid direct sunlight. Make sure of no damage, corrosion, leaks on the receptacles.

Take necessary measures for preventing cargo shift.

**ADR****Limited quantities (LQ):** 5L**Excepted quantities (EQ)** Code: E2

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 500 ml

**Transport category:** 2**Tunnel restriction code:** D/E**IMDG****Limited quantities (LQ)** 5L**Excepted quantities (EQ)** Code: E2

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 500 ml

**UN "Model Regulation":** UN 1263 PAINT, 3, II**\* SECTION 15: Regulatory information****15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

No further relevant information available.

**Dutch List of Substances of Very High Concern (ZZS)**

None of the ingredients is listed.

Printing date 16.03.2023

Version number 1

Revision: 16.03.2023

**Trade name: DAI-EL LATEX GLP-103SR****Labelling according to Regulation (EC) No 1272/2008***The product is classified and labelled according to the CLP regulation.***Hazard pictograms**

GHS02 GHS07 GHS08

**Signal word** Danger**Hazard-determining components of labelling:**

Toluene

Isopropyl alcohol

**Hazard statements**

H225 Highly flammable liquid and vapour.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H361d Suspected of damaging the unborn child.

H336 May cause drowsiness or dizziness.

H373 May cause damage to organs through prolonged or repeated exposure.

H304 May be fatal if swallowed and enters airways.

**Precautionary statements**

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P241 Use explosion-proof [electrical/ventilating/lighting] equipment.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

**Seveso category** P5c FLAMMABLE LIQUIDS**DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II***None of the ingredients is listed.***Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))***None of the ingredients is listed.***Annex II - REPORTABLE EXPLOSIVES PRECURSORS***None of the ingredients is listed.***Regulation (EC) No 273/2004 on drug precursors**

CAS: 108-88-3 Toluene: 3

**Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors**

CAS: 108-88-3 Toluene: 3

*National regulations* No further information available.**15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.**\* SECTION 16: Other information**

The product is for the industrial use only. We do not guarantee the safety in case the product is used for the other purposes. When using the product for health-care application or food/feed application, consult us in advance. This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.



Printing date 16.03.2023

Version number 1

Revision: 16.03.2023

**Trade name: DAI-EL LATEX GLP-103SR**

**Department issuing SDS:** EHS Department

**Contact:**

<http://www.daikin.com/>

[sales@daikinchem.de](mailto:sales@daikinchem.de)

[www.daikinchem.de](http://www.daikinchem.de)

**Abbreviations and acronyms:**

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 2: Flammable liquids – Category 2

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Repr. 2: Reproductive toxicity – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2

Asp. Tox. 1: Aspiration hazard – Category 1

**\* Data compared to the previous version altered.**