

Printing date 31.03.2023 Version number 1 Revision: 31.03.2023

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name: POLYFLON PTFE TT-7400 THINNER FOR TC-7400 SERIES

1.2 Relevant identified uses of the substance or mixture and uses advised against:

No further relevant information available.

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier:

DAIKIN INDUSTRIES, LTD. CHEMICALS DIVISION:

OSAKA UMEDA TWIN TOWERS SOUTH, 1-13-1 Umeda, Kita-ku, Osaka-shi, Osaka, 530-0001, Japan

Phone: +81-6-6147-9702 Fax: +81-6-6147-9807

Further information obtainable from: http://www.daikin.com/

1.4 Emergency telephone number:

Japan: +81-6-6349-7521

China: +86-532-8388-9090, +86-21-34151689

South Korea: +82-2-568-1722

Americas: CHEMTREC +1-800-424-9300 (Outside US/Canada: +1-703-527-3887)

Europe: +49-211-179 225-0

SECTION 2: Hazard identification

2.1 Classification of the substance or mixture Classification according to Regulation (EC) No 1272/2008



Flam. Liq. 3 H226 Flammable liquid and vapour.



Repr. 2 H361d Suspected of damaging the unborn child.

STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.



Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2 H319 Causes serious eye irritation.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008:

The product is classified and labelled according to the CLP regulation.

Signal word: Danger

Hazard-determining components of labelling:

Toluene

Precautionary statements:

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.



Printing date 31.03.2023 Version number 1 Revision: 31.03.2023

Trade name: POLYFLON PTFE TT-7400 THINNER FOR TC-7400 SERIES

SECTION 3: Composition/information on ingredients

Information on ingredients:

CAS: 112-34-5 2-(2-Butoxyethoxy)ethanol

65-75%

Eye Irrit. 2, H319

CAS: 123-42-2 4-Hydroxy-4-methylpentan-2-one

15-25%

Flam. Liq. 3, H226 Eye Irrit. 2, H319

Specific concentration limit: Eye Irrit. 2; H319: $C \ge 10 \%$

CAS: 108-88-3 Toluene

5-15%

Flam. Liq. 2, H225

Repr. 2, H361d; STOT RE 2, H373; Asp. Tox. 1, H304

Skin Irrit. 2, H315; STOT SE 3, H336

Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General information: Seek medical treatment.

After inhalation: Supply fresh air; consult doctor in case of complaints.

After skin contact:

Remove contaminated clothes immediately.

Immediately wash with water and soap and rinse thoroughly.

Consult a doctor in case of complaints.

After eye contact:

Immediately rinse with a lot of water for several minutes. Remove contact lenses if possible. Continue rinsing. Consult an ophthalmologist in case of complaints.

After swallowing:

Rinse mouth with water. Do not induce vomiting.

Consult a doctor in case of complaints.

4.2 Most important symptoms and effects, both acute and chronic: No further relevant information available.

4.3 Indication of any immediate medical attention and special treatment needed:

No further relevant information available.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing agents:

Alcohol resistant foam

Fire-extinguishing powder

Dry sand

CO2

For safety reasons unsuitable extinguishing agents: Water with full jet

5.2 Special hazards arising from the substance or mixture:

Formation of toxic gases is possible during heating or in case of fire.

Receptacle may explode when heated.

Extremely flammable; can ignite easily with heat, sparks, fire.

5.3 Advice for firefighters: Remove receptacles from area of fire if possible.

Protective equipment:

Wear self-contained breathing apparatus and protective suit.

Do not inhale explosion gases or combustion gases.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures:

Ensure adequate ventilation before entering the area.

Stay on the windward side.



Printing date 31.03.2023 Version number 1 Revision: 31.03.2023

Trade name: POLYFLON PTFE TT-7400 THINNER FOR TC-7400 SERIES

Keep out unauthorized persons.

Wear appropriate protective devices (See Section 8 Exposure Controls/Personal Protection).

Avoid contact with eyes and skin.

Do not swallow the product.

6.2 Environmental precautions: Prevent seepage into sewage system, workpits and cellars.

6.3 Methods and material for containment and cleaning up:

Do not flush with water or aqueous cleansing agents

For a small amount of leakage: Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders) or collect in an empty container that can be sealed tightly.

For a small amount of leakage: Use clean anti-static tools when absorbing the product.

For a large amount of leakage: Enclose with banks to avoid outflow. Lead the leakage to a safe place and collect.

Remove ignition sources immediately.

Ground all equipment when the product leaks.

There is a danger of explosion. Prepare fire extinguisher in case of emergency.

6.4 Reference to other sections:

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

7.1 Precautions for safe handling:

Prevent formation of aerosols.

Ensure good ventilation/exhaustion at the workplace.

Handle with care. Avoid jolting, friction and impact.

Do not handle until all safety precautions have been read and understood.

Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Use flame proof electric/lighting devices and ventilation equipment.

Ground/bond container and receiving equipment.

7.2 Conditions for safe storage, including any incompatibilities:

Storage

Requirements to be met by storerooms and receptacles:

Store in a cool and dry location.

Prevent any seepage into the ground.

 ${\it Use only receptacles specifically permitted for this substance/product.}$

Keep containers tightly sealed.

Information about storage in one common storage facility:

Store away from oxidising agents.

See section 10 for information on incompatible materials.

Further information about storage conditions:

Protect from heat and direct sunlight.

Store containers in a well ventilated area.

Store locked up.

7.3 Specific end use(s): No further relevant information available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters No further information available.

Ingredients with limit values that require monitoring at the workplace:

CAS: 112-34-5 2-(2-Butoxyethoxy)ethanol

IOELV (EU) Short-term value: 101.2 mg/m³, 15 ppm Long-term value: 67.5 mg/m³, 10 ppm

8.2 Exposure controls

Appropriate engineering controls No further data; see item 7.

Individual protection measures, such as personal protective equipment

General protective and hygienic measures:

Wash hands before breaks and at the end of work.



Printing date 31.03.2023 Version number 1 Revision: 31.03.2023

Trade name: POLYFLON PTFE TT-7400 THINNER FOR TC-7400 SERIES

Do not eat or drink while working. Keep away from tobacco products.

Respiratory protection:

Use respiratory protective device with filters for organic and acid gas (or airline respirators in some cases) if formation of toxic gases is possible while the product is heated.

Use respiratory protective device with organic gas cartridge.

Hand protection



Material of gloves: Rubber

Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

Eye/face protection



Body protection: Protective work clothing

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

General Information

Physical state
Colour:
Transparent
Odour:
Aromatic
Not determined.
Melting point/freezing point:
Which is a point or initial boiling point and boiling range
Flammability
Flammability
Fluid
Transparent
Aromatic
Not determined.
Undetermined.
Not applicable.

Lower and upper explosion limit

Lower explosive limit:0.9 Vol %Upper explosive limit:8.1 Vol %Flash point:36 °C (TCC)Ignition temperature:225 °C

Decomposition temperature: No further information available.

pH Not determined.

Viscosity:

Kinematic viscosityNot determined.Dynamic:Not determined.

Solubility

water: No further information available.

Partition coefficient n-octanol/water (log value) No further information available.

Vapour pressure at 20 °C: 29 hi

No further information available.

Density and/or relative density

Density at 20 °C:0.938 g/cm³Not determined.Relative densityNot determined.Vapour densityNot determined.

Particle characteristics No further information available.

9.2 Other information:

Form: Liquid

Auto-ignition temperature: Product is not self-igniting.



Printing date 31.03.2023 Version number 1 Revision: 31.03.2023

Trade name: POLYFLON PTFE TT-7400 THINNER FOR TC-7400 SERIES

Explosive properties: Product is not explosive. However, formation of explosive

air/vapour mixtures are possible.

Evaporation rate Not determined.

Information with regard to physical hazard classes

ExplosivesNot applicableFlammable gasesNot applicableAerosolsNot applicableOxidising gasesNot applicableGases under pressureNot applicable

Flammable liquids

Flammable liquid and vapour.

Flammable solidsNot applicableSelf-reactive substances and mixturesNot applicablePyrophoric liquidsNot applicablePyrophoric solidsNot applicableSelf-heating substances and mixturesNot applicable

Substances and mixtures, which emit flammable gases

in contact with waterNot applicableOxidising liquidsNot applicableOxidising solidsNot applicableOrganic peroxidesNot applicableCorrosive to metalsNot applicableDesensitised explosivesNot applicable

SECTION 10: Stability and reactivity

10.1 Reactivity No further relevant information available.

10.2 Chemical stability

Thermal decomposition / conditions to be avoided: To avoid thermal decomposition do not overheat.

10.3 Possibility of hazardous reactions: No dangerous reactions known under normal conditions of use.

10.4 Conditions to avoid: Keep away from heat, sparks, flame, high temperature.

10.5 Incompatible materials: Oxidizing agents

10.6 Hazardous decomposition products: Danger of toxic fluorine based pyrolysis products.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity no data

LD/LC50 values relevant for classification:

CAS: 112-34-5 2-(2-Butoxyethoxy)ethanol

Oral LD50 5660 mg/kg (Rat)
Dermal LD50 4000 mg/kg (Rabbit)

CAS: 108-88-3 Toluene

Oral LD50 5000 mg/kg (Rat) Dermal LD50 12124 mg/kg (Rabbit) Inhalative LC50/4h 5320 ppm (Mouse)

Skin corrosion/irritation:

Causes skin irritation.

Serious eye damage/irritation:

Causes serious eye irritation.

Respiratory or skin sensitisation: Based on available data, the classification criteria are not met.

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Carcinogenicity: Based on available data, the classification criteria are not met.

Reproductive toxicity:

Suspected of damaging the unborn child.

STOT-single exposure: Based on available data, the classification criteria are not met.



Printing date 31.03.2023 Version number 1 Revision: 31.03.2023

Trade name: POLYFLON PTFE TT-7400 THINNER FOR TC-7400 SERIES

STOT-repeated exposure:

May cause damage to organs through prolonged or repeated exposure.

Aspiration hazard:

May be fatal if swallowed and enters airways.

Other information (about experimental toxicology): No further information available.

Subacute to chronic toxicity: No further information available.

11.2 Information on other hazards: Endocrine disrupting properties:

None of the ingredients is listed.

SECTION 12: Ecological information

12.1 Toxicity

Aquatic toxicity: No further relevant information available.

12.2 Persistence and degradability: No further relevant information available.

12.3 Bioaccumulative potential: No further relevant information available.

12.4 Mobility in soil: No further relevant information available.

12.5 Results of PBT and vPvB assessment

PBT: No further relevant information available.

vPvB: No further information available.

12.6 Endocrine disrupting properties For information on endocrine disrupting properties see section 11.

12.7 Other adverse effects: Ecotoxical effects: no data

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Recommendation: Disposal must be made according to official regulations.

Uncleaned packaging

Recommendation: Disposal must be made according to official regulations.

SECTION 14: Transport information

14.1 UN number or ID number

ADR, IMDG, IATA UN1263

14.2 UN proper shipping name:

ADR: 1263 PAINT RELATED MATERIAL IMDG, IATA PAINT RELATED MATERIAL

14.3 Transport hazard class(es):

ADR



Class: 3 (F1) Flammable liquids.

Label:

IMDG, IATA



Class: 3 Flammable liquids.

Label: 3

14.4 Packing group:

ADR, IMDG, IATA

14.5 Environmental hazards:

Marine pollutant: No



Printing date 31.03.2023 Revision: 31.03.2023 Version number 1

Trade name: POLYFLON PTFE TT-7400 THINNER FOR TC-7400 SERIES

14.6 Special precautions for user: Warning: Flammable liquids.

Hazard identification number (Kemler code): EMS Number: *F-E,S-E*

14.7 Maritime transport in bulk according to IMO

Not applicable. instruments

Transport/Additional information: Avoid direct sunlight. Make sure of no damage, corrosion, leaks

on the receptacles.

Take necessary measures for preventing cargo shift.

ADR

5LLimited quantities (LQ): Code: E1 Excepted quantities (EQ)

> Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml

Transport category: D/ETunnel restriction code:

IMDG

5LLimited quantities (LQ) Code: E1 Excepted quantities (EQ)

> Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml

UN1263, PAINT RELATED MATERIAL, 3, III UN "Model Regulation":

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

No further relevant information available.

Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

Hazard pictograms







GHS02

GHS07

GHS08

Signal word Danger

Hazard-determining components of labelling:

Toluene

Hazard statements

H226 Flammable liquid and vapour.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H361d Suspected of damaging the unborn child.

H373 May cause damage to organs through prolonged or repeated exposure.

H304 May be fatal if swallowed and enters airways.

Precautionary statements

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P210

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

National regulations No further information available.

15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.



Printing date 31.03.2023 Version number 1 Revision: 31.03.2023

Trade name: POLYFLON PTFE TT-7400 THINNER FOR TC-7400 SERIES

SECTION 16: Other information

The product is for the industrial use only. We do not guarantee the safety in case the product is used for the other purposes. When using the product for health-care application or food/feed application, consult us in advance. This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Department issuing SDS: Planning Dept.

Contact: http://www.daikin.com/ Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 3: Flammable liquids – Category 3 Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Repr. 2: Reproductive toxicity – Category 2

STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2

Asp. Tox. 1: Aspiration hazard - Category 1

* Data compared to the previous version altered.