

Printing date 21.12.2016

Version number 1

Revision: 25.01.2016

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1 Product identifier****Trade name: NEOFLON PFA TC-7609M1****Article number: TC7609M1****1.2 Relevant identified uses of the substance or mixture and uses advised against:**

No further relevant information available.

1.3 Details of the supplier of the safety data sheet**Manufacturer/Supplier:**

DAIKIN INDUSTRIES, LTD. CHEMICALS DIVISION:

Umeda Center Bldg., 4-12, Nakazaki-Nishi 2-chome, Kita-Ku, Osaka, JAPAN

Phone: (+81) 6-6373-4345 Fax: (+81) 6-6373-4281

Further information obtainable from: <http://www.daikin.com/>**1.4 Emergency telephone number:**

Japan: +81-6-6349-7521

China: +86-512-5-232-0949, +86-21-34151689

South Korea: +82-2-568-1722

Americas: +1-256-306-5000

Europe: +49-211-179 225-0

SECTION 2: Hazard identification**2.1 Classification of the substance or mixture****Classification according to Regulation (EC) No 1272/2008**

Flam. Liq. 2 H225 Highly flammable liquid and vapour.



Muta. 1B H340 May cause genetic defects.

Carc. 1B H350 May cause cancer.

Repr. 1B H360D May damage the unborn child.



Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2 H319 Causes serious eye irritation.

STOT SE 3 H335 May cause respiratory irritation.

2.2 Label elements**Labelling according to Regulation (EC) No 1272/2008:**

The product is classified and labelled according to the CLP regulation.

Signal word: Danger**Precautionary statements:**

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P241 Use explosion-proof electrical/ventilating/lighting equipment.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

Printing date 21.12.2016

Version number 1

Revision: 25.01.2016

Trade name: NEOFLON PFA TC-7609M1

Additional information:

Restricted to professional users.

SECTION 3: Composition/information on ingredients**Information on ingredients:**

26655-00-5 Perfluoro(alkoxy alkane)	5-15%
<i>Binder</i>	5-15%
1333-86-4 Carbon black	<5%
127-19-5 <i>N,N</i> -Dimethylacetamide	25-35%
<i>T Repr. Cat. 2 R61; Xn R20/21</i>	
<i>Repr. 1B, H360D</i>	
<i>Acute Tox. 4, H312; Acute Tox. 4, H332</i>	
872-50-4 <i>N</i> -Methyl-2-pyrrolidone	10-20%
<i>T Repr. Cat. 2 R61; Xi R36/37/38</i>	
<i>Repr. 1B, H360D</i>	
<i>Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335</i>	
108-10-1 Methyl isobutyl ketone	10-20%
<i>Xn R20; Xi R36/37; F R11</i>	
<i>R66</i>	
<i>Flam. Liq. 2, H225</i>	
<i>Acute Tox. 4, H332; Eye Irrit. 2, H319; STOT SE 3, H335</i>	
78-93-3 Butanone	10-20%
<i>Xi R36; F R11</i>	
<i>R66-67</i>	
<i>Flam. Liq. 2, H225</i>	
<i>Eye Irrit. 2, H319; STOT SE 3, H336</i>	
<i>Others</i>	<5%

SVHC:127-19-5 *N,N*-Dimethylacetamide872-50-4 *N*-Methyl-2-pyrrolidone**Additional information:** For the wording of the listed hazard phrases refer to section 16.**SECTION 4: First aid measures****4.1 Description of first aid measures****General information:** Seek medical treatment.**After inhalation:** Supply fresh air; consult doctor in case of complaints.**After skin contact:**

Remove contaminated clothes immediately.

Immediately wash with water and soap and rinse thoroughly.

Consult a doctor in case of complaints.

After eye contact:

Immediately rinse with a lot of water for several minutes. Remove contact lenses if possible. Continue rinsing.

Consult an ophthalmologist in case of complaints.

After swallowing:

Rinse mouth with water. Do not induce vomiting.

Consult a doctor in case of complaints.

4.2 Most important symptoms and effects, both acute and chronic: No further relevant information available.**4.3 Indication of any immediate medical attention and special treatment needed:**

No further relevant information available.

Printing date 21.12.2016

Version number 1

Revision: 25.01.2016

Trade name: NEOFLON PFA TC-7609M1

SECTION 5: Firefighting measures**5.1 Extinguishing media****Suitable extinguishing agents:**

Alcohol resistant foam

Dry sand

Fire-extinguishing powder

CO₂**For safety reasons unsuitable extinguishing agents:** Water with full jet**5.2 Special hazards arising from the substance or mixture:**

During heating or in case of fire poisonous gases may be produced.

Formation of toxic gases is possible during heating or in case of fire.

Receptacle may explode when heated.

Extremely flammable; can ignite easily with heat, sparks, fire.

5.3 Advice for firefighters: Remove receptacles from area of fire if possible.**Protective equipment:**

Wear self-contained breathing apparatus and protective suit.

Do not inhale explosion gases or combustion gases.

SECTION 6: Accidental release measures**6.1 Personal precautions, protective equipment and emergency procedures:**

Ensure adequate ventilation before entering the area.

Stay on the windward side.

Keep out unauthorized persons.

Wear appropriate protective devices (See Section 8 Exposure Controls/Personal Protection).

Avoid contact with eyes and skin.

Do not swallow the product.

6.2 Environmental precautions: Prevent seepage into sewage system, workpits and cellars.**6.3 Methods and material for containment and cleaning up:**

Do not flush with water or aqueous cleansing agents

For a small amount of leakage: Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders) or collect in an empty container that can be sealed tightly.

For a small amount of leakage: Use clean anti-static tools when absorbing the product.

For a large amount of leakage: Enclose with banks to avoid outflow. Lead the leakage to a safe place and collect.

Remove ignition sources immediately.

Ground all equipment when the product leaks.

There is a danger of explosion. Prepare fire extinguisher in case of emergency.

6.4 Reference to other sections:

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage**7.1 Precautions for safe handling:**

Prevent formation of aerosols.

Ensure good ventilation/exhaustion at the workplace.

Handle with care. Avoid jolting, friction and impact.

Do not handle until all safety precautions have been read and understood.

Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Use flame proof electric/lighting devices and ventilation equipment.

Ground/bond container and receiving equipment.

7.2 Conditions for safe storage, including any incompatibilities:**Storage****Requirements to be met by storerooms and receptacles:**

Store in a cool and dry location.

Printing date 21.12.2016

Version number 1

Revision: 25.01.2016

Trade name: NEOFLON PFA TC-7609M1

Provide solvent resistant, sealed floor.

Keep containers tightly sealed.

Information about storage in one common storage facility:

Store away from oxidising agents.

See section 10 for information on incompatible materials.

Further information about storage conditions:

Protect from heat and direct sunlight.

Store containers in a well ventilated area.

Store locked up.

7.3 Specific end use(s): No further relevant information available.

SECTION 8: Exposure controls/personal protection

Additional information about design of technical facilities: No further data; see item 7.

8.1 Control parameters No further information available.

Ingredients with limit values that require monitoring at the workplace:

127-19-5 N,N-Dimethylacetamide

OEL (Japan) Long-term value: 36 mg/m³, 10 ppm

PEL (USA) Long-term value: 35 mg/m³, 10 ppm
Skin

REL (USA) Long-term value: 35 mg/m³, 10 ppm
Skin

TLV (USA) Long-term value: 36 mg/m³, 10 ppm
Skin; BEI

108-10-1 Methyl isobutyl ketone

OEL (Japan) Long-term value: 200 mg/m³, 50 ppm

PEL (USA) Long-term value: 410 mg/m³, 100 ppm

REL (USA) Short-term value: 300 mg/m³, 75 ppm
Long-term value: 205 mg/m³, 50 ppm

TLV (USA) Short-term value: 307 mg/m³, 75 ppm
Long-term value: 82 mg/m³, 20 ppm
BEI

872-50-4 N-Methyl-2-pyrrolidone

OEL (Japan) Long-term value: 4 mg/m³, 1 ppm

WEEL (USA) Long-term value: 10 ppm
Skin

78-93-3 Butanone

OEL (Japan) Long-term value: 590 mg/m³, 200 ppm

PEL (USA) Long-term value: 590 mg/m³, 200 ppm

REL (USA) Short-term value: 885 mg/m³, 300 ppm
Long-term value: 590 mg/m³, 200 ppm

TLV (USA) Short-term value: 885 mg/m³, 300 ppm
Long-term value: 590 mg/m³, 200 ppm
BEI

Ingredients with biological limit values:

127-19-5 N,N-Dimethylacetamide

BEI (USA) 30 mg/g creatinine

Medium: urine

Time: end of shift at end of workweek

Parameter: N-Methylacetamide

Printing date 21.12.2016

Version number 1

Revision: 25.01.2016

Trade name: **NEOFLON PFA TC-7609M1****108-10-1 Methyl isobutyl ketone**

OEL-B (Japan) 1,7 mg/l

試料: urine

試料採取時期: End of shift

物質: Methylisobutylketone

BEI (USA) 1 mg/L

Medium: urine

Time: end of shift

Parameter: MIBK

872-50-4 N-Methyl-2-pyrrolidone

BEI (USA) 100 mg/L

Medium: urine

Time: end of shift

Parameter: 5-Hydroxy-N-methyl-2-pyrrolidone

78-93-3 Butanone

OEL-B (Japan) 5 mg/l

試料: urine

試料採取時期: End of shift or a few hours after high exposure

物質: Methyl ethyl ketone

BEI (USA) 2 mg/L

Medium: urine

Time: end of shift

Parameter: MEK

Additional information: The lists valid during the making were used as basis.**8.2 Exposure controls****Personal protective equipment****General protective and hygienic measures:**

Wash hands before breaks and at the end of work.

Do not eat or drink while working.

Keep away from tobacco products.

Respiratory protection:

Use respiratory protective device with filters for organic and acid gas (or airline respirators in some cases) if formation of toxic gases is possible while the product is heated.

Use respiratory protective device with organic gas cartridge.

Protection of hands:

Protective gloves

Material of gloves: Rubber**Eye protection:**

Safety glasses

Body protection: Protective work clothing**SECTION 9: Physical and chemical properties****9.1 Information on basic physical and chemical properties****General Information****Appearance****Form:** Liquid**Colour:** Black

Printing date 21.12.2016

Version number 1

Revision: 25.01.2016

Trade name: NEOFLON PFA TC-7609M1

Odour:	Characteristic
pH-value:	No further information available.
Melting point/freezing point:	No further information available.
Initial boiling point and boiling range:	No further information available.
Flash point:	5,8 °C (SCC)
Flammability (solid, gas):	Not applicable.
Explosion limits:	
Lower explosive limit:	1,8 Vol % (N,N-dimethylacetamide)
Upper explosive limit:	11,5 Vol % (N,N-dimethylacetamide)
Vapour pressure:	-
Density:	No further information available.
Solubility in / Miscibility with water:	No further information available.
Partition coefficient: n-octanol/water:	No further information available.
9.2 Other information:	No further relevant information available.

SECTION 10: Stability and reactivity

10.1 Reactivity No further relevant information available.

10.2 Chemical stability

Thermal decomposition / conditions to be avoided: To avoid thermal decomposition do not overheat.

10.3 Possibility of hazardous reactions: No dangerous reactions known under normal conditions of use.

10.4 Conditions to avoid: Keep away from heat, sparks, flame, high temperature.

10.5 Incompatible materials: Oxidizing agents

10.6 Hazardous decomposition products:

As for decomposition products, particulate matters and extremely toxic/corrosive fumes may be generated (HF, carbonyl fluoride, monomers, perfluoroisobutylene).

Decomposition products differ depending on the temperature and conditions.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity no data

LD/LC50 values relevant for classification:

127-19-5 N,N-Dimethylacetamide

Oral LD50 4930 mg/kg (Rat)

Dermal LD50 2240 mg/kg (Rabbit)

108-10-1 Methyl isobutyl ketone

Oral LD50 2080 mg/kg (Rat)

Dermal LD50 16000 mg/kg (rab)

Inhalative LC50/4 h 8,3-16,6 ppm (Rat)

872-50-4 N-Methyl-2-pyrrolidone

Oral LD50 3914 mg/kg (Rat)

Dermal LD50 8000 mg/kg (Rabbit)

Low boiling point naphtha - unspecified

Oral LD50 >6800 mg/kg (Rat)

Dermal LD50 >3400 mg/kg (rab)

Inhalative LC50/4 h >10,2 ppm (Rat)

Printing date 21.12.2016

Version number 1

Revision: 25.01.2016

Trade name: NEOFLON PFA TC-7609M1**Primary irritant effect****Skin corrosion/irritation**

Causes skin irritation.

Serious eye damage/irritation

Causes serious eye irritation.

after inhalation: No further information available.**Respiratory or skin sensitisation** Based on available data, the classification criteria are not met.**Additional toxicological information:**

General effects:

Fumes generated during burning may cause "polymer fume fever" (flu-like symptoms such as fever, chill, cough).

This may last for a whole day and night.

Fumes are not absorbed in skin. No sensitizing effect known.

Effects of hydrogen fluoride:

Low concentration of hydrogen fluoride may cause feeling of dyspnea, cough, irritation in eyes, nose, throat, fever, chill for 1-2 days.

After that, dyspnea, cyanosis and pulmonary edema may be seen.

High concentration of hydrogen fluoride damages liver and kidney.

Effects of carbonyl fluoride:

Skin: Irritation or eruption

Eye: Ulcer in cornea, conjunctiva

Respiratory system : Irritation

Lung: Temporary symptoms such as cough, pain, dyspnea

Persons who have experienced lung diseases are vulnerable to toxicity caused by excessive exposure to pyrolysis products

CMR effects**Germ cell mutagenicity**

May cause genetic defects.

Carcinogenicity

May cause cancer.

Reproductive toxicity

May damage the unborn child.

STOT-single exposure

May cause respiratory irritation.

STOT-repeated exposure Based on available data, the classification criteria are not met.**Aspiration hazard** Based on available data, the classification criteria are not met.**Chronic study** No further information available.**SECTION 12: Ecological information****12.1 Toxicity****Aquatic toxicity:** No further relevant information available.**12.2 Persistence and degradability:** No further relevant information available.**12.3 Bioaccumulative potential:** No further relevant information available.**12.4 Mobility in soil:** No further relevant information available.**12.5 Results of PBT and vPvB assessment****PBT:** No further relevant information available.**vPvB:** No further relevant information available.**12.6 Other adverse effects:** No further relevant information available.**SECTION 13: Disposal considerations****13.1 Waste treatment methods****Recommendation:** Disposal must be made according to official regulations.**Uncleaned packaging****Recommendation:** Disposal must be made according to official regulations.

Printing date 21.12.2016

Version number 1

Revision: 25.01.2016

Trade name: **NEOFLON PFA TC-7609M1****SECTION 14: Transport information****14.1 UN-Number:**
ADR, IMDG, IATA UN1263**14.2 UN proper shipping name:**
ADR: 1263 PAINT
IMDG, IATA PAINT**14.3 Transport hazard class(es):**
ADR, IMDG, IATA**Class:** 3 Flammable liquids.**14.4 Packing group:**
ADR, IMDG, IATA II**14.5 Environmental hazards:**
Marine pollutant: No**14.6 Special precautions for user:** Warning: Flammable liquids.**14.7 Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code:** Not applicable.**Transport/Additional information:** Avoid direct sunlight. Make sure of no damage, corrosion, leaks on the receptacles.
Take necessary measures for preventing cargo shift.**ADR****Limited quantities (LQ):** 5L**Excepted quantities (EQ)** Code: E2

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 500 ml

UN "Model Regulation": UN1263, PAINT, 3, II**SECTION 15: Regulatory information****15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**
Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

Hazard pictograms

GHS02



GHS07



GHS08

Signal word Danger**Hazard-determining components of labelling:**

N,N-Dimethylacetamide

N-Methyl-2-pyrrolidone

Low boiling point naphtha - unspecified

Hazard statements

H225 Highly flammable liquid and vapour.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H340 May cause genetic defects.

H350 May cause cancer.

H360D May damage the unborn child.

H335 May cause respiratory irritation.

Printing date 21.12.2016

Version number 1

Revision: 25.01.2016

Trade name: NEOFLON PFA TC-7609M1**Precautionary statements**

- P210 *Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.*
- P241 *Use explosion-proof electrical/ventilating/lighting equipment.*
- P303+P361+P353 *IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.*
- P305+P351+P338 *IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.*
- P405 *Store locked up.*
- P501 *Dispose of contents/container in accordance with local/regional/national/international regulations.*

Other regulations, limitations and prohibitive regulations:**Substances of very high concern (SVHC) according to REACH, Article 57:**

127-19-5 N,N-Dimethylacetamide

872-50-4 N-Methyl-2-pyrrolidone

SECTION 16: Other information

The product is for the industrial use only. We do not guarantee the safety in case the product is used for the other purposes. When using the product for health-care application or food/feed application, consult us in advance. This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Department issuing SDS: EHS Department**Contact:** <http://www.daikin.com/>**Abbreviations and acronyms:**

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

SVHC: Substances of Very High Concern

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 2: Flammable liquids – Category 2

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Muta. 1B: Germ cell mutagenicity – Category 1B

Carc. 1B: Carcinogenicity – Category 1B

Repr. 1B: Reproductive toxicity – Category 1B

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3