

Revision: 14.05.2019

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name: POLYFLON PTFE EK-1983S21RArticle number: EK1983S21R1.2 Relevant identified uses of the substance or mixture and uses advised against:No further relevant information available.

1.3 Details of the supplier of the safety data sheet Manufacturer/Supplier: DAIKIN INDUSTRIES, LTD. CHEMICALS DIVISION: Umeda Center Bldg., 4-12, Nakazaki-Nishi 2-chome, Kita-Ku, Osaka, JAPAN Phone: (+81) 6-6373-4345 Fax: (+81) 6-6373-4281

Further information obtainable from: http://www.daikin.com/ *1.4 Emergency telephone number: Japan:* +81-6-6349-7521 *China:* +86-512-5-232-0949, +86-21-34151689 *South Korea:* +82-2-568-1722 *Americas: CHEMTREC* +1-800-424-9300 (*Outside US/Canada:* +1-703-527-3887) *Europe:* +49-211-179 225-0

SECTION 2: Hazard identification

2.1 Classification of the substance or mixture Classification according to Regulation (EC) No 1272/2008



Repr. 1B H360D May damage the unborn child.



Skin Irrit. 2 H315Causes skin irritation.Eye Irrit. 2 H319Causes serious eye irritation.STOT SE 3 H335May cause respiratory irritation.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008:

The product is classified and labelled according to the CLP regulation. *Signal word:* Danger

Hazard-determining components of labelling:

N-Methyl-2-pyrrolidone Precautionary statements:

Precautionary statements:P261Avoid breathing dust/fume/gas/mist/vapours/spray.P280Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.P304+P340IF INHALED: Remove person to fresh air and keep comfortable for breathing.P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present
and easy to do. Continue rinsing.P405Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

Additional information:

Restricted to professional users.



Trade name: POLYFLON PTFE EK-1983S21R

Information on i	ngredients:	
CAS: 9002-84-0	Polytetrafluoroethylene	10-209
	Binder	5-15%
	Polyoxyethene glycol alkyl ether	<5%
CAS: 13463-67-7	Titanium dioxide	<5%
CAS: 7631-86-9	Silicon dioxide	<5%
CAS: 1333-86-4	Carbon black	<5%
CAS: 872-50-4	N-Methyl-2-pyrrolidone Repr. 1B, H360D Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335	15-25
CAS: 7732-18-5	Water	40-509
SVHC:	Others	5-15%
	-Methyl-2-pyrrolidone nation: For the wording of the listed hazard phrases refer to section 16.	

4.1 Description of first aid measures General information: Seek medical treatment. After inhalation: Supply fresh air; consult doctor in case of complaints. After skin contact: Remove contaminated clothes immediately. Immediately wash with water and soap and rinse thoroughly. Consult a doctor in case of complaints. After eye contact: Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor. Immediately rinse with a lot of water for several minutes. Remove contact lenses if possible. Continue rinsing. Consult an ophthalmologist in case of complaints. After swallowing: Rinse mouth with water. Do not induce vomiting. Consult a doctor in case of complaints. 4.2 Most important symptoms and effects, both acute and chronic: No further relevant information available. 4.3 Indication of any immediate medical attention and special treatment needed: No further relevant information available.

SECTION 5: Firefighting measures

5.1 Extinguishing media
Suitable extinguishing agents: Use fire extinguishing methods suitable for surrounding conditions.
For safety reasons unsuitable extinguishing agents: No further information available.
5.2 Special hazards arising from the substance or mixture:
Formation of toxic gases is possible during heating or in case of fire.
5.3 Advice for firefighters:
Protective equipment:
Wear fully protective suit.
Wear self-contained breathing apparatus and protective suit.
Do not inhale explosion gases or combustion gases.



Version number 1

Revision: 14.05.2019

Trade name: POLYFLON PTFE EK-1983S21R

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures: Ensure adequate ventilation before entering the area. Do not inhale explosion gases or combustion gases. Keep out unauthorized persons. Wear appropriate protective devices (See Section 8 Exposure Controls/Personal Protection). Avoid contact with eyes and skin. Do not swallow the product. **6.2** Environmental precautions: Do not allow to enter sewers/surface or ground water. Prevent seepage into sewage system, workpits and cellars. 6.3 Methods and material for containment and cleaning up: For a small amount of leakage: Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders) or collect in an empty container that can be sealed tightly. For a large amount of leakage: Enclose with banks to avoid outflow. Lead the leakage to a safe place and collect. 6.4 Reference to other sections: See Section 7 for information on safe handling. See Section 8 for information on personal protection equipment. See Section 13 for disposal information.

SECTION 7: Handling and storage

7.1 Precautions for safe handling:

Prevent formation of aerosols. Ensure good ventilation/exhaustion at the workplace. Do not handle until all safety precautions have been read and understood. Information about fire - and explosion protection: Keep ignition sources away - Do not smoke. 7.2 Conditions for safe storage, including any incompatibilities: Storage Requirements to be met by storerooms and receptacles: Store in a cool and dry location. Provide solvent resistant, sealed floor. Keep containers tightly sealed. Information about storage in one common storage facility: No further information available. See section 10 for information on incompatible materials. Further information about storage conditions: Store in cool, dry conditions in well sealed receptacle. Protect from heat and direct sunlight. Store containers in a well ventilated area. Store locked up. 7.3 Specific end use(s): No further relevant information available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters No further information available. Additional information about design of technical facilities: No further data; see item 7. Ingredients with limit values that require monitoring at the workplace:

CAS: 872-50-4 N-Methyl-2-pyrrolidone OEL (Japan) Long-term value: 4 mg/m³, 1 ppm WEEL (USA) Long-term value: 10 ppm Skin



Revision: 14.05.2019

Trade name: POLYFLON PTFE EK-1983S21R

Ingredients with biological limit values:

CAS: 872-50-4 N-Methyl-2-pyrrolidone

BEI (USA) 100 mg/L Medium: urine Time: end of shift Parameter: 5-Hydroxy-N-methyl-2-pyrrolidone

8.2 Exposure controls Personal protective equipment General protective and hygienic measures: Wash hands before breaks and at the end of work. Do not eat or drink while working. Keep away from tobacco products. Respiratory protection: Use respiratory protective device with filters for or

Use respiratory protective device with filters for organic and acid gas (or airline respirators in some cases) if formation of toxic gases is possible while the product is heated. Use respiratory protective device with organic gas cartridge. **Protection of hands:**



Protective gloves

Material of gloves: Rubber Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed. Eye protection:



Body protection: Protective work clothing

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties General Information

Appearance Form: Liquid Colour: Brown **Odour:** Aromatic **Odour threshold:** Not determined. *pH-value*: 3-6 *Melting point/freezing point:* No further information available. Initial boiling point and boiling range: No further information available. Not applicable. Flash point: Flammability (solid, gas): Not applicable. **Decomposition temperature:** No further information available. Auto-ignition temperature: Product is not selfigniting. Product does not present an explosion hazard. **Explosive properties: Explosion limits:** Lower explosive limit: No further information available. Upper explosive limit: No further information available. Vapour pressure: No further information available.



Version number 1

Revision: 14.05.2019

Trade name: POLYFLON PTFE EK-1983S21R

Density: Relative density Vapour density Evaporation rate	No further information available. Not determined. Not determined. Not determined.
Solubility in / Miscibility with water:	No further information available.
Partition coefficient: n-octanol/water: Viscosity:	No further information available.
Dynamic:	Not determined.
Kinematic:	Not determined.
9.2 Other information:	No further relevant information available.

SECTION 10: Stability and reactivity

10.1 Reactivity No further relevant information available.

10.2 Chemical stability

Thermal decomposition / conditions to be avoided: To avoid thermal decomposition do not overheat.

10.3 Possibility of hazardous reactions: No dangerous reactions known under normal conditions of use.

10.4 Conditions to avoid: Keep away from heat, sparks, flame, high temperature.

10.5 Incompatible materials: No further relevant information available.

10.6 Hazardous decomposition products:

Fluorophosgene in contact with naked flame or red hot objects.

As for decomposition products, particulate matters and extremely toxic/corrosive fumes may be generated (HF, carbonyl fluoride, monomers, perfluoroisobutylene).

Decomposition products differ depending on the temperature and conditions.

SECTION 11: Toxicological information

11.1 Information on toxicological effects Acute toxicity no data LD/LC50 values relevant for classification:

CAS: 872-50-4 N-Methyl-2-pyrrolidone

Oral LD50 3914 mg/kg (Rat) Dermal LD50 8000 mg/kg (Rabbit) Primary irritant effect Skin corrosion/irritation Causes skin irritation. Serious eye damage/irritation Causes serious eye irritation. Respiratory or skin sensitisation Based on available data, the classification criteria are not met. Other information (about experimental toxicology): No further information available. Subacute to chronic toxicity No further information available. Additional toxicological information: General effects: Fumes generated during burning may cause "polymer fume fever" (flu-like symptons such as fever, chill, cough). This may last for a whole day and night. Fumes are not absorbed in skin. No sensitizing effect known.

Effects of hydrogen fluoride: Low concentration of hydrogen fluoride may cause feeling of dyspnea, cough, irritation in eyes, nose, throat, fever, chill for 1-2 days. After that, dyspnea, cyanosis and pulmonary edema may be seen. High concentration of hydrogen fluoride damages liver and kidney.

Effects of carbonyl fluoride: Skin: Irritation or eruption Eye: Ulcer in cornea, conjunctiva



Version number 1

Revision: 14.05.2019

Trade name: POLYFLON PTFE EK-1983S21R

Respiratory system: Irritation Lung: Temporary symptons such as cough, pain, dyspnea Persons who have experienced lung diseases are vulnerable to toxicity caused by excessive exposure to pyrolysis products CMR effects Germ cell mutagenicity Based on available data, the classification criteria are not met. Carcinogenicity Based on available data, the classification criteria are not met. Reproductive toxicity May damage the unborn child. STOT-single exposure May cause respiratory irritation. STOT-repeated exposure Based on available data, the classification criteria are not met. Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

12.1 Toxicity Aquatic toxicity: No further relevant information available. 12.2 Persistence and degradability: No further relevant information available. 12.3 Bioaccumulative potential: No further relevant information available. 12.4 Mobility in soil: No further relevant information available. Other information Ecotoxical effects: no data 12.5 Results of PBT and vPvB assessment **PBT**: No further relevant information available. No further relevant information available. Not applicable. vPvB: No further relevant information available. No further relevant information available. Not applicable. 12.6 Other adverse effects: No further relevant information available.

SECTION 13: Disposal considerations

13.1 Waste treatment methods Recommendation: Disposal must be made according to official regulations.

Uncleaned packaging Recommendation: Disposal must be made according to official regulations.

SECTION 14: Transport information

14.1 UN-Number:	
ADR, ADN, IMDG, IATA	Not applicable
14.2 UN proper shipping name:	
ADR, ADN, IMDG, IATA	Not applicable
14.3 Transport hazard class(es):	
ADR, ADN, IMDG, IATA	
Class:	Not applicable
14.4 Packing group:	
ADR, IMDG, IATA	Not applicable
14.5 Environmental hazards:	
Marine pollutant:	No
14.6 Special precautions for user:	Not applicable.
14.7 Transport in bulk according to Annex II of	
MARPOL73/78 and the IBC Code:	Not applicable.



Revision: 14.05.2019

Trade name: POLYFLON PTFE EK-1983S21R

Transport/Additional information:	Avoid direct sunlight. Make sure of no damage, corrosion, leaks on the receptacles.
UN "Model Regulation":	Take necessary measures for preventing cargo shift. Not applicable

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture No further relevant information available. Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation. Hazard pictograms



Signal word Danger

Hazard-determining components of labelling: N-Methyl-2-pyrrolidone Hazard statements H315 Causes skin irritation. H319 Causes serious eye irritation. H360D May damage the unborn child. H335 May cause respiratory irritation. **Precautionary statements** P261 Avoid breathing dust/fume/gas/mist/vapours/spray. P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection. P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing. P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P405 Store locked up. P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

National regulations No further information available.

Other regulations, limitations and prohibitive regulations: 尚未进行化学物质安全性评价 Substances of very high concern (SVHC) according to REACH, Article 57:

CAS: 872-50-4 N-Methyl-2-pyrrolidone

15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

The product is for the industrial use only. We do not guarantee the safety in case the product is used for the other purposes. When using the product for health-care application or food/feed application, consult us in advance. This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Department issuing SDS: EHS Department

Contact: http://www.daikin.com/

Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)

ICAO: International Civil Aviation Organisation ICAO-TI: Technical Instructions by the "International Civil Aviation Organisation" (ICAO)

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association



Version number 1

Revision: 14.05.2019

Trade name: POLYFLON PTFE EK-1983S21R

GHS: Globally Harmonised System of Classification and Labelling of Chemicals LC50: Lethal concentration, 50 percent DS0: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic SVHC: Substances of Very High Concern vPvB: very Persistent and very Bioaccumulative Skin Irrit. 2: Skin corrosion/irritation – Category 2 Eye Irrit. 2: Serious eye damage/eye irritation – Category 2 Repr. 1B: Reproductive toxicity – Category 1B STOT SE 3: Specific target organ toxicity (single exposure) – Category 3 *** Data compared to the previous version altered.**