

Printing date 20.10.2025

Version number 1

Revision: 20.10.2025

* SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name: OPTOOL DAC-200

1.2 Relevant identified uses of the substance or mixture and uses advised against:

Sector of Use SU8 Manufacture of bulk, large scale chemicals (including petroleum products)

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier:

DAIKIN INDUSTRIES, LTD. CHEMICALS DIVISION:

OSAKA UMEDA TWIN TOWERS SOUTH, 1-13-1 Umeda, Kita-ku, Osaka-shi, Osaka, 530-0001, Japan

Phone: +81-6-6147-9702 Fax: +81-6-6147-9807

1.4 Emergency telephone number: Japan: +81-6-6349-7521

* SECTION 2: Hazard identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008



GHS02

Flam. Liq. 2 H225 Highly flammable liquid and vapour.



GHS07

Eye Irrit. 2 H319 Causes serious eye irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008:

The product is classified and labelled according to the CLP regulation.

Signal word: Danger

Hazard-determining components of labelling:

Butanone

Precautionary statements:

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P241 Use explosion-proof [electrical/ventilating/lighting] equipment.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

Additional information:

The synthetic polymer microparticles supplied are subject to conditions laid down by entry 78 of Annex XVII to Regulation (EC) No 1907/2006 of the European Parliament and of the Council.

* SECTION 3: Composition/information on ingredients

Information on ingredients:

Fluorocompound	15-25%
CAS: 108-65-6 2-methoxy-1-methylethyl acetate	41-50%
Flam. Liq. 3, H226	
CAS: 78-93-3 Butanone	30-39%
Flam. Liq. 2, H225	
Eye Irrit. 2, H319; STOT SE 3, H336	
EUH066	

Printing date 20.10.2025

Version number 1

Revision: 20.10.2025

Trade name: OPTOOL DAC-200

*Additional information: For the wording of the listed hazard phrases refer to section 16.**** SECTION 4: First aid measures****4.1 Description of first aid measures****General information:** Seek medical treatment.**After inhalation:**

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

Supply fresh air; consult doctor in case of complaints.

After skin contact:

Remove contaminated clothes immediately.

Immediately wash with water and soap and rinse thoroughly.

Consult a doctor in case of complaints.

After eye contact:

Immediately rinse with a lot of water for several minutes. Remove contact lenses if possible. Continue rinsing.

Consult an ophthalmologist in case of complaints.

After swallowing:

Rinse mouth with water. Do not induce vomiting.

Consult a doctor in case of complaints.

4.2 Most important symptoms and effects, both acute and chronic: Allergic reactions**4.3 Indication of any immediate medical attention and special treatment needed:**

No further relevant information available.

SECTION 5: Firefighting measures**5.1 Extinguishing media****Suitable extinguishing agents:**

Foam

Fire-extinguishing powder

CO₂**For safety reasons unsuitable extinguishing agents:** High pressure water jet**5.2 Special hazards arising from the substance or mixture:**

Formation of toxic gases is possible during heating or in case of fire.

Receptacle may explode when heated.

Extremely flammable; can ignite easily with heat, sparks, fire.

5.3 Advice for firefighters: Remove receptacles from area of fire if possible.**Protective equipment:**

Wear self-contained breathing apparatus and protective suit.

Do not inhale explosion gases or combustion gases.

SECTION 6: Accidental release measures**6.1 Personal precautions, protective equipment and emergency procedures:**

Ensure adequate ventilation before entering the area.

Stay on the windward side.

Keep out unauthorized persons.

Wear appropriate protective devices (See Section 8 Exposure Controls/Personal Protection).

Avoid contact with eyes and skin.

Do not swallow the product.

6.2 Environmental precautions:

Do not allow to enter sewers/surface water or groundwater.

Prevent seepage into sewage system, workpits and cellars.

6.3 Methods and material for containment and cleaning up:

Do not flush with water or aqueous cleansing agents

For a small amount of leakage: Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders) or collect in an empty container that can be sealed tightly.

For a small amount of leakage: Use clean anti-static tools when absorbing the product.

For a large amount of leakage: Enclose with banks to avoid outflow. Lead the leakage to a safe place and collect.

Remove ignition sources immediately.

Printing date 20.10.2025

Version number 1

Revision: 20.10.2025

Trade name: OPTOOL DAC-200

Ground all equipment when the product leaks.

There is a danger of explosion. Prepare fire extinguisher in case of emergency.

6.4 Reference to other sections:

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

*** SECTION 7: Handling and storage****7.1 Precautions for safe handling:**

Ensure good ventilation/exhaustion at the workplace.

Handle with care. Avoid jolting, friction and impact.

Do not handle until all safety precautions have been read and understood.

Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Use flame proof electric/lighting devices and ventilation equipment.

Ground/bond container and receiving equipment.

7.2 Conditions for safe storage, including any incompatibilities:**Storage****Requirements to be met by storerooms and receptacles:**

Store in a cool and dry location.

Provide solvent resistant, sealed floor.

Prevent any seepage into the ground.

Keep containers tightly sealed.

Information about storage in one common storage facility:

Store away from oxidising agents.

See section 10 for information on incompatible materials.

Further information about storage conditions:

Protect from heat and direct sunlight.

Store containers in a well ventilated area.

Store locked up.

7.3 Specific end use(s): No further relevant information available.

*** SECTION 8: Exposure controls/personal protection**

8.1 Control parameters No further information available.

Ingredients with limit values that require monitoring at the workplace:

CAS: 78-93-3 Butanone

IOELV (EU) Short-term value: 900 mg/m³, 300 ppm

Long-term value: 600 mg/m³, 200 ppm

8.2 Exposure controls

Appropriate engineering controls No further data; see section 7.

Individual protection measures, such as personal protective equipment**General protective and hygienic measures:**

Wash hands before breaks and at the end of work.

Do not eat or drink while working.

Keep away from tobacco products.

Respiratory protection:

Use respiratory protective device with filters for organic and acid gas (or airline respirators in some cases) if formation of toxic gases is possible while the product is heated.

Use respiratory protective device with organic gas cartridge.

Hand protection

Protective gloves

Material of gloves: Rubber

Printing date 20.10.2025

Version number 1

Revision: 20.10.2025

Trade name: OPTOOL DAC-200

Eye/face protection



Safety glasses

Body protection: Protective work clothing

* SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

General Information

Physical state

Liquid

Colour:

Light yellow

Odour:

Characteristic

Odour threshold:

Not determined.

Melting point/freezing point:

Undetermined.

Boiling point or initial boiling point and boiling range

No further information available.

Flammability

Not applicable.

Lower and upper explosion limit

Lower explosive limit:

No further information available.

Upper explosive limit:

Not determined.

Flash point:

2.5 °C (TCC)

Auto-ignition temperature:

No further information available.

Decomposition temperature:

No further information available.

Not determined.

pH

Not determined.

Not determined.

Viscosity:

Kinematic viscosity

Not determined.

Dynamic:

Not determined.

Solubility

water:

No further information available.

Partition coefficient n-octanol/water (log value)

No further information available.

Vapour pressure:

No further information available.

Vapour pressure:

No further information available.

Density and/or relative density

Density:

Not determined.

Relative density

Not determined.

Vapour density

Not determined.

Particle characteristics

No further information available.

9.2 Other information:

Form:

Liquid

Ignition temperature:

Product is not self-igniting.

Explosive properties:

Product is not explosive. However, formation of explosive air/vapour mixtures are possible.

Evaporation rate

Not determined.

Information with regard to physical hazard classes

Explosives

Not applicable

Flammable gases

Not applicable

Aerosols

Not applicable

Oxidising gases

Not applicable

Gases under pressure

Not applicable

Flammable liquids

Highly flammable liquid and vapour.

Flammable solids

Not applicable

Self-reactive substances and mixtures

Not applicable

Pyrophoric liquids

Not applicable

Pyrophoric solids

Not applicable

Printing date 20.10.2025

Version number 1

Revision: 20.10.2025

Trade name: OPTOOL DAC-200

Self-heating substances and mixtures	Not applicable
Substances and mixtures, which emit flammable gases in contact with water	Not applicable
Oxidising liquids	Not applicable
Oxidising solids	Not applicable
Organic peroxides	Not applicable
Corrosive to metals	Not applicable
Desensitised explosives	Not applicable

SECTION 10: Stability and reactivity**10.1 Reactivity** No further relevant information available.**10.2 Chemical stability****Thermal decomposition / conditions to be avoided:** To avoid thermal decomposition do not overheat.**10.3 Possibility of hazardous reactions:**

Danger of polymerisation.

No dangerous reactions known under normal conditions of use.

10.4 Conditions to avoid: Keep away from heat, sparks, flame, high temperature.**10.5 Incompatible materials:**

Strong acids, strong alkali, amines and alkali metals

Oxidizing agents

10.6 Hazardous decomposition products:

As for decomposition products, particulate matters and extremely toxic/corrosive fumes may be generated (HF, carbonyl fluoride, monomers, perfluoroisobutylene).

Decomposition products differ depending on the temperature and conditions.

*** SECTION 11: Toxicological information****11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008****Acute toxicity** Based on available data, the classification criteria are not met.**LD/LC50 values relevant for classification:** No further information available.**Primary irritant effect****Skin corrosion/irritation:** No further information available.**Serious eye damage/irritation:** Causes serious eye irritation.**Respiratory or skin sensitisation:** No sensitizing effect.**STOT-single exposure:** May cause drowsiness or dizziness.**STOT-repeated exposure:** No further information available.**Other information (about experimental toxicology):** No further information available.**Subacute to chronic toxicity:** No further information available.**Additional toxicological information:**

General effects:

Fumes generated during burning may cause "polymer fume fever" (flu-like symptoms such as fever, chill, cough). This may last for a whole day and night.

Fumes are not absorbed in skin. No sensitizing effect known.

Effects of hydrogen fluoride:

Low concentration of hydrogen fluoride may cause feeling of dyspnea, cough, irritation in eyes, nose, throat, fever, chill for 1-2 days.

After that, dyspnea, cyanosis and pulmonary edema may be seen.

High concentration of hydrogen fluoride damages liver and kidney.

Effects of carbonyl fluoride:

Skin: Irritation or eruption

Eye: Ulcer in cornea, conjunctiva

Respiratory system: Irritation

Lung: Temporary symptoms such as cough, pain, dyspnea

Persons who have experienced lung diseases are vulnerable to toxicity caused by excessive exposure to pyrolysis products

Printing date 20.10.2025

Version number 1

Revision: 20.10.2025

Trade name: OPTOOL DAC-200

* SECTION 12: Ecological information

12.1 Toxicity

Aquatic toxicity: No further relevant information available.

12.2 Persistence and degradability: No further relevant information available.

12.3 Bioaccumulative potential: No further relevant information available.

12.4 Mobility in soil: No further relevant information available.

12.5 Results of PBT and vPvB assessment

PBT: No further relevant information available.

vPvB: No further information available.

12.7 Other adverse effects:

Ecotoxicological effects: no data

Remark: Harmful to fish

Additional ecological information:

General notes: Harmful to aquatic organisms

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Recommendation: Disposal must be made according to official regulations.

Uncleaned packaging

Recommendation: Disposal must be made according to official regulations.

* SECTION 14: Transport information

14.1 UN number or ID number

ADR, IMDG, IATA

UN1993

14.2 UN proper shipping name:

ADR, IMDG, IATA

FLAMMABLE LIQUID, N.O.S. (Butanone)

14.3 Transport hazard class(es):

ADR



Class:

3 (F1) Flammable liquids.

Label:

3

IMDG, IATA



Class:

3 Flammable liquids.

Label:

3

14.4 Packing group:

ADR, IMDG, IATA

II

14.5 Environmental hazards:

Marine pollutant:

No

14.6 Special precautions for user:

Warning: Flammable liquids.

Hazard identification number (Kemler code):

33

EMS Number:

F-E,S-E

Stowage Category

B

14.7 Maritime transport in bulk according to IMO instruments

Not applicable.

Transport/Additional information:

Avoid direct sunlight. Make sure of no damage, corrosion, leaks on the receptacles.

Take necessary measures for preventing cargo shift.

Printing date 20.10.2025

Version number 1

Revision: 20.10.2025

Trade name: OPTOOL DAC-200

ADR

Limited quantities (LQ):

Excepted quantities (EQ)

IL

Code: E2

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 500 ml

Transport category:

2

Tunnel restriction code:

D/E

IMDG

Limited quantities (LQ)

Excepted quantities (EQ)

IL

Code: E2

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 500 ml

UN "Model Regulation":

UN 1993 FLAMMABLE LIQUID, N.O.S. (Butanone), 3, II

* SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

No further relevant information available.

Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

Hazard pictograms



GHS02 GHS07

Signal word Danger

Hazard-determining components of labelling:

Butanone

Hazard statements

H225 Highly flammable liquid and vapour.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P241 Use explosion-proof [electrical/ventilating/lighting] equipment.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

Seveso category P5c FLAMMABLE LIQUIDS

DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II

None of the ingredients is listed.

National regulations No further information available.

15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

* SECTION 16: Other information

The product is for the industrial use only. We do not guarantee the safety in case the product is used for the other purposes. When using the product for health-care application or food/feed application, consult us in advance.

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Department issuing SDS: EHS Department

Printing date 20.10.2025

Version number 1

Revision: 20.10.2025

Trade name: OPTOOL DAC-200**Contact:** <https://www.daikin.com/>**Abbreviations and acronyms:**

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 2: Flammable liquids – Category 2

Acute Tox. 4: Acute toxicity – Category 4

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Skin Sens. 1: Skin sensitisation – Category 1

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

*** Data compared to the previous version altered.**