

Printing date 31.03.2023 Version number 1 Revision: 31.03.2023

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name: DEMNUM S-20, S-65, S-200

Article number: DMS

1.2 Relevant identified uses of the substance or mixture and uses advised against:

No further relevant information available.

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier:

DAIKIN INDUSTRIES, LTD. CHEMICALS DIVISION:

OSAKA UMEDA TWIN TOWERS SOUTH, 1-13-1 Umeda, Kita-ku, Osaka-shi, Osaka, 530-0001, Japan

Phone: +81-6-6147-9702 Fax: +81-6-6147-9807

Further information obtainable from: http://www.daikin.com/

1.4 Emergency telephone number:

Japan: +81-6-6349-7521

China: +86-532-8388-9090, +86-21-34151689

South Korea: +82-2-568-1722

Americas: CHEMTREC +1-800-424-9300 (Outside US/Canada: +1-703-527-3887)

Europe: +49-211-179 225-0

SECTION 2: Hazard identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008

The substance is not classified, according to the CLP regulation.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008: Not applicable

Signal word: Not applicable

SECTION 3: Composition/information on ingredients

Information on ingredients:

CAS: 113114-19-5 Perfluoroalkyl polyether

> = 99%

SECTION 4: First aid measures

4.1 Description of first aid measures

General information: Seek medical treatment.

After inhalation: Supply fresh air; consult doctor in case of complaints.

After skin contact:

Immediately wash with water and soap and rinse thoroughly.

Remove contaminated clothes immediately.

After eye contact:

Immediately rinse with a lot of water for several minutes. Remove contact lenses if possible. Continue rinsing. **After swallowing:** Rinse mouth with water. Do not induce vomiting.

4.2 Most important symptoms and effects, both acute and chronic: No further relevant information available.

4.3 Indication of any immediate medical attention and special treatment needed:

No further relevant information available.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing agents: Use fire extinguishing methods suitable for surrounding conditions.

5.2 Special hazards arising from the substance or mixture:

Formation of toxic gases is possible during heating or in case of fire.

5.3 Advice for firefighters:

Protective equipment:

Wear self-contained breathing apparatus and protective suit.

Do not inhale explosion gases or combustion gases.



Printing date 31.03.2023 Version number 1 Revision: 31.03.2023

Trade name: DEMNUM S-20, S-65, S-200

Wear fully protective suit.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures:

Ensure adequate ventilation before entering the area.

Stay on the windward side.

Keep out unauthorized persons.

Wear appropriate protective devices (See Section 8 Exposure Controls/Personal Protection).

Avoid contact with eyes and skin.

Do not swallow the product.

6.2 Environmental precautions: Prevent seepage into sewage system, workpits and cellars.

6.3 Methods and material for containment and cleaning up:

For a small amount of leakage: Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders) or collect in an empty container that can be sealed tightly.

For a large amount of leakage: Enclose with banks to avoid outflow. Lead the leakage to a safe place and collect.

6.4 Reference to other sections:

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

7.1 Precautions for safe handling:

Ensure good ventilation/exhaustion at the workplace.

Do not handle until all safety precautions have been read and understood.

Information about fire - and explosion protection: Keep ignition sources away - Do not smoke.

7.2 Conditions for safe storage, including any incompatibilities:

Storage

Requirements to be met by storerooms and receptacles:

Store in a cool and dry location.

Keep containers tightly sealed.

Information about storage in one common storage facility:

See section 10 for information on incompatible materials.

Further information about storage conditions:

Store in cool, dry conditions in well sealed receptacle.

Protect from heat and direct sunlight.

Store containers in a well ventilated area.

Store locked up.

7.3 Specific end use(s): No further relevant information available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Ingredients with limit values that require monitoring at the workplace: Not required.

8.2 Exposure controls

Appropriate engineering controls No further data; see item 7.

Individual protection measures, such as personal protective equipment

General protective and hygienic measures:

Wash hands before breaks and at the end of work.

Do not eat or drink while working.

Keep away from tobacco products.

Respiratory protection:

Use respiratory protective device with filters for organic and acid gas (or airline respirators in some cases) if formation of toxic gases is possible while the product is heated.

Use respiratory protective device with organic gas cartridge.



Printing date 31.03.2023 Version number 1 Revision: 31.03.2023

Trade name: DEMNUM S-20, S-65, S-200

Hand protection



Material of gloves: Rubber

Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

Eye/face protection



Body protection: Protective work clothing

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

General Information

Physical stateFluidColour:ColourlessOdour:OdourlessOdour threshold:Not determined.Melting point/freezing point:<-53 °C</th>Boiling point or initial boiling point and boiling rangeUndetermined.FlammabilityNot applicable.

Lower and upper explosion limit

Lower explosive limit: No further information available.

Upper explosive limit:Not determined.Flash point:Not applicable.Ignition temperature:>600 °C

Decomposition temperature: No further information available.

pH Not determined.

Viscosity:

Kinematic viscosity Dynamic:Not determined.
Not determined.

Solubility

water: No further information available.

Partition coefficient n-octanol/water (log value) No further information available.

Vapour pressure at 20 °C:

Density and/or relative density

Density at 20 °C:1.85 g/cm³Relative density1.85-1.90Vapour densityNot determined.

Particle characteristics No further information available.

9.2 Other information:

Form: Liquid Auto-ignition temperature: >600 °C

Explosive properties: Product does not present an explosion hazard.

0.001 hPa

Evaporation rate Not determined.

Information with regard to physical hazard classes

ExplosivesNot applicableFlammable gasesNot applicableAerosolsNot applicableOxidising gasesNot applicableGases under pressureNot applicableFlammable liquidsNot applicable



Printing date 31.03.2023 Version number 1 Revision: 31.03.2023

Trade name: DEMNUM S-20, S-65, S-200

Flammable solidsNot applicableSelf-reactive substances and mixturesNot applicablePyrophoric liquidsNot applicablePyrophoric solidsNot applicableSelf-heating substances and mixturesNot applicable

Substances and mixtures, which emit flammable gases

in contact with waterNot applicableOxidising liquidsNot applicableOxidising solidsNot applicableOrganic peroxidesNot applicableCorrosive to metalsNot applicableDesensitised explosivesNot applicable

SECTION 10: Stability and reactivity

10.1 Reactivity No further relevant information available.

10.2 Chemical stability

Thermal decomposition / conditions to be avoided:

Even at the temperatures reached during the normal hot processing of fluoropolymers, fume that presents a potential health hazard may be generated.

To avoid thermal decomposition do not overheat.

10.3 Possibility of hazardous reactions: No dangerous reactions known under normal conditions of use.

10.4 Conditions to avoid: Keep away from heat, sparks, flame, high temperature.

10.5 Incompatible materials: No further relevant information available.

10.6 Hazardous decomposition products: Danger of toxic fluorine based pyrolysis products.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity no data

LD/LC50 values relevant for classification:

CAS: 113114-19-5 Perfluoroalkyl polyether

Oral LD50 >2000 mg/kg (Rat)
Dermal LD50 >2000 mg/kg (Rat)

Skin corrosion/irritation:

No irritant effect.

CAS: 113114-19-5 Perfluoroalkyl polyether

Irritation of skin Primary skin irritation study No irritation (Rabbit)

No irritation

Irritation of eyes Primary eye irritation study No irritation (Rabbit)

No irritation

Serious eye damage/irritation: Based on available data, the classification criteria are not met.

Respiratory or skin sensitisation:

CAS: 113114-19-5 Perfluoroalkyl polyether

Sensitisation Skin Sensitization (Guinea pig)

No skin sensitization

Germ cell mutagenicity: Based on available data, the classification criteria are not met. Carcinogenicity: Based on available data, the classification criteria are not met. Reproductive toxicity: Based on available data, the classification criteria are not met. STOT-single exposure: Based on available data, the classification criteria are not met. STOT-repeated exposure: Based on available data, the classification criteria are not met.

Aspiration hazard: Based on available data, the classification criteria are not met.

Other information (about experimental toxicology): Chromosomal Aberration Study in vitro- Negative



Printing date 31.03.2023 Version number 1 Revision: 31.03.2023

Trade name: DEMNUM S-20, S-65, S-200

11.2 Information on other hazards: Endocrine disrupting properties:

Substance is not listed.

SECTION 12: Ecological information

12.1 Toxicity

Aquatic toxicity:

CAS: 113114-19-5 Perfluoroalkyl polyether

NOEL 102 mg/l (Alga)

72 hr

> 100 mg/l (Daphnia)

48 hr

> 100 mg/l (Fish)

Zebra fish 96 hr

12.2 Persistence and degradability: No further relevant information available.

Other information:

The product is slightly biodegradable.

Activated Sludge, Respiration Inhibition NOEC > 1000 mg/L

12.3 Bioaccumulative potential: No further relevant information available.

12.4 Mobility in soil: No further relevant information available.

12.5 Results of PBT and vPvB assessment

PBT: No further relevant information available.

vPvB: No further information available.

12.6 Endocrine disrupting properties For information on endocrine disrupting properties see section 11.

12.7 Other adverse effects: Ecotoxical effects: no data

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Recommendation: Disposal must be made according to official regulations.

Uncleaned packaging

Recommendation: Disposal must be made according to official regulations.

SECTION 14: Transport information

14.1 UN number or ID number

ADR, ADN, IMDG, IATA Not applicable

14.2 UN proper shipping name:

ADR, ADN, IMDG, IATA

Not applicable

14.3 Transport hazard class(es):

ADR, ADN, IMDG, IATA

Class: Not applicable

14.4 Packing group:
ADR, IMDG, IATA
Not applicable

14.5 Environmental hazards:

Marine pollutant: No

14.6 Special precautions for user: Not applicable.

14.7 Maritime transport in bulk according to IMO

instruments Not applicable.

Transport/Additional information: Avoid direct sunlight. Make sure of no damage, corrosion, leaks

on the receptacles.

Take necessary measures for preventing cargo shift.

UN "Model Regulation": Not applicable



Printing date 31.03.2023 Version number 1 Revision: 31.03.2023

Trade name: DEMNUM S-20, S-65, S-200

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

No further relevant information available.

Labelling according to Regulation (EC) No 1272/2008 Not applicable

Hazard pictograms Not applicable

Signal word Not applicable

Hazard statements Not applicable

15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

The product is for the industrial use only. We do not guarantee the safety in case the product is used for the other purposes. When using the product for health-care application or food/feed application, consult us in advance. This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Department issuing SDS: EHS Department

Contact: http://www.daikin.com/ Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative

^{*} Data compared to the previous version altered.