

Printing date 31.03.2022 Version number 6 Revision: 31.03.2022

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name: <u>UNIDYNE XF-5003</u> Article number: <u>UNXF5003 STD2</u>

1.2 Relevant identified uses of the substance or mixture and uses advised against:

No further relevant information available.

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier:

DAIKIN INDUSTRIES, LTD. CHEMICALS DIVISION:

Umeda Center Bldg., 4-12, Nakazaki-Nishi 2-chome, Kita-Ku, Osaka, JAPAN

Phone: (+81) 6-6373-4345 Fax: (+81) 6-6373-4281

Further information obtainable from: http://www.daikin.com/

1.4 Emergency telephone number:

Japan: +81-6-6349-7521

China: +86-512-5-232-0949, +86-21-34151689

South Korea: +82-2-568-1722

Americas: CHEMTREC +1-800-424-9300 (Outside US/Canada: +1-703-527-3887)

Europe: +49-211-179 225-0

SECTION 2: Hazard identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008:

The product is classified and labelled according to the CLP regulation.

Signal word: Not applicable **Precautionary statements:**

P273 Avoid release to the environment.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

Additional information:

EUH208 Contains 5-chloro-2-methyl-2H-isothiazol-3-one, 2-methyl-2H-isothiazol-3-one. May produce an allergic reaction.

* SECTION 3: Composition/information on ingredients

Information on ingredients:

CAS: 7732	2-18-5 Water	55-65%
	Acrylate copolymer	20 – 30%
CAS: 24800-44-0 Tripropylene glycol		5-15%
CAS: 67-6	63-0 Isopropyl alcohol Flam. Liq. 2, H225 Eye Irrit. 2, H319; STOT SE 3, H336	< 0.5%
	Others	< 5%

Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General information: Seek medical treatment.

After inhalation: Supply fresh air; consult doctor in case of complaints.

After skin contact:

Remove contaminated clothes immediately.

Immediately wash with water and soap and rinse thoroughly.



Printing date 31.03.2022 Version number 6 Revision: 31.03.2022

Trade name: UNIDYNE XF-5003

Consult a doctor in case of complaints.

After eye contact:

Immediately rinse with a lot of water for several minutes. Remove contact lenses if possible. Continue rinsing. Consult an ophthalmologist in case of complaints.

After swallowing:

Rinse mouth with water. Do not induce vomiting.

Consult a doctor in case of complaints.

4.2 Most important symptoms and effects, both acute and chronic: No further relevant information available.

4.3 Indication of any immediate medical attention and special treatment needed:

No further relevant information available.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing agents: Use fire extinguishing methods suitable for surrounding conditions.

5.2 Special hazards arising from the substance or mixture:

Formation of toxic gases is possible during heating or in case of fire.

5.3 Advice for firefighters:

Protective equipment:

Wear self-contained breathing apparatus and protective suit.

Do not inhale explosion gases or combustion gases.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures:

Ensure adequate ventilation before entering the area.

Stay on the windward side.

Keep out unauthorized persons.

Wear appropriate protective devices (See Section 8 Exposure Controls/Personal Protection).

Avoid contact with eyes and skin.

Do not swallow the product.

6.2 Environmental precautions: Prevent seepage into sewage system, workpits and cellars.

6.3 Methods and material for containment and cleaning up:

For a small amount of leakage: Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders) or collect in an empty container that can be sealed tightly.

For a large amount of leakage: Enclose with banks to avoid outflow. Lead the leakage to a safe place and collect.

6.4 Reference to other sections:

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

7.1 Precautions for safe handling:

Ensure good ventilation/exhaustion at the workplace.

Do not handle until all safety precautions have been read and understood.

Information about fire - and explosion protection: Keep ignition sources away - Do not smoke.

7.2 Conditions for safe storage, including any incompatibilities:

Storage

Requirements to be met by storerooms and receptacles:

Store in a cool and dry location.

Prevent any seepage into the ground.

Keep containers tightly sealed.

Information about storage in one common storage facility:

See section 10 for information on incompatible materials.

Further information about storage conditions:

Protect from heat and direct sunlight.

Store containers in a well ventilated area.

Store locked up.

7.3 Specific end use(s): No further relevant information available.



Printing date 31.03.2022 Version number 6 Revision: 31.03.2022

Trade name: UNIDYNE XF-5003

SECTION 8: Exposure controls/personal protection

8.1 Control parameters No further information available.

Ingredients with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

8.2 Exposure controls

Appropriate engineering controls No further data; see item 7.

Individual protection measures, such as personal protective equipment

General protective and hygienic measures:

Wash hands before breaks and at the end of work.

Do not eat or drink while working. Keep away from tobacco products.

Respiratory protection:

Use respiratory protective device with filters for organic and acid gas (or airline respirators in some cases) if formation of toxic gases is possible while the product is heated.

Use respiratory protective device with organic gas cartridge.

Hand protection



Material of gloves: Rubber

Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed. **Eye/face protection**



Body protection: Protective work clothing

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

General Information

Physical stateFluidColour:Light yellowOdour:AromaticOdour threshold:Not determined.

*Melting point/freezing point:*No further information available.

Boiling point or initial boiling point and boiling range 100 °C (Water) **Flammability** Not applicable.

Lower and upper explosion limit

Lower explosive limit:No further information available.Upper explosive limit:No further information available.

Flash point: Not applicable.

Auto-ignition temperature:Product is not selfigniting.Decomposition temperature:No further information available.

pH at $20 \, ^{\circ}C$ 2.5

Viscosity:

Kinematic viscosity

Dynamic:

Not determined.

Not determined.

Solubility

water:
Partition coefficient n-octanol/water (log value)
Vapour pressure:
No further information available.
No further information available.
No further information available.



Printing date 31.03.2022 Version number 6 Revision: 31.03.2022

Trade name: UNIDYNE XF-5003

Density and/or relative density

Density at 20 °C: 1.07 g/cm³

No further information available.

Relative densityNot determined. **Vapour density**Not determined.

9.2 Other information:

Appearance

Form: Liquid

Explosive properties: Product does not present an explosion hazard.

Evaporation rate Not determined.

Information with regard to physical hazard classes

Not applicable **Explosives** Not applicable Flammable gases Not applicable Aerosols Not applicable Oxidising gases Gases under pressure Not applicable Not applicable Flammable liquids Not applicable Flammable solids Not applicable Self-reactive substances and mixtures Not applicable Pyrophoric liquids Pyrophoric solids Not applicable Self-heating substances and mixtures Not applicable

Substances and mixtures, which emit flammable gases

in contact with waterNot applicableOxidising liquidsNot applicableOxidising solidsNot applicableOrganic peroxidesNot applicableCorrosive to metalsNot applicableDesensitised explosivesNot applicable

SECTION 10: Stability and reactivity

10.1 Reactivity No further relevant information available.

10.2 Chemical stability

Thermal decomposition / conditions to be avoided: To avoid thermal decomposition do not overheat.

10.3 Possibility of hazardous reactions: No dangerous reactions known under normal conditions of use.

10.4 Conditions to avoid: Keep away from heat, sparks, flame, high temperature.

10.5 Incompatible materials: No further relevant information available.

10.6 Hazardous decomposition products: Carbon monoxide

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

LD/LC50 values relevant for classification:

 $Oral\ LD50 > 2000\ mg/kg\ (Rat)$

Skin corrosion/irritation

Irritation of skin Primary skin irritation study (Rabbit)

Mild irritant(OECD404)

Serious eye damage/irritation

Irritation of eyes Primary eye irritation study (Rabbit)

Mild irritant(OECD405)

after inhalation: No further information available.

Respiratory or skin sensitisation

Sensitisation Skin Sensitization SI (Mouse)

Non sensitiser(OECD429)

Carcinogenicity No further information available.



Printing date 31.03.2022 Version number 6 Revision: 31.03.2022

Trade name: UNIDYNE XF-5003

Reproductive toxicity No further information available. STOT-single exposure No further information available.

STOT-repeated exposure No further information available.

Aspiration hazard No further information available.

Other information (about experimental toxicology): Bacterial Reverse Mutation Test: negative

Subacute to chronic toxicity No further information available.

11.2 Information on other hazards Endocrine disrupting properties

None of the ingredients is listed.

SECTION 12: Ecological information

12.1 Toxicity

Aquatic toxicity:

EC50 mg/l (Alga) 9.53 mg/L 48hr 10.2 mg/L 72hr non-GLP

> > 5000 mg/l (Bacteria) OECD209 non-GLP

12.2 Persistence and degradability:

Biodegradation 99 % (Activated sludge)

28days non-GLP

12.3 Bioaccumulative potential: No further relevant information available.

12.4 Mobility in soil: No further relevant information available.

12.5 Results of PBT and vPvB assessment

PBT: No further relevant information available. v**PvB:** No further relevant information available.

12.6 Endocrine disrupting properties For information on endocrine disrupting properties see section 11.

Ecotoxical effects: no data Remark: Harmful to fish

Additional ecological information:

General notes: Harmful to aquatic organisms

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Recommendation: Disposal must be made according to official regulations.

Uncleaned packaging

Recommendation: Disposal must be made according to official regulations.

SECTION 14: Transport information

14.1 UN number or ID number

ADR, IMDG, IATA Not applicable

14.2 UN proper shipping name:

ADR, IMDG, IATA Not applicable

14.3 Transport hazard class(es):

ADR, ADN, IMDG, IATA

Class: Not applicable

14.4 Packing group:

ADR, IMDG, IATA Not applicable

14.5 Environmental hazards:

Marine pollutant: No

14.6 Special precautions for user: Not applicable.



Printing date 31.03.2022 Version number 6 Revision: 31.03.2022

Trade name: UNIDYNE XF-5003

14.7 Maritime transport in bulk according to IMO

instruments Not applicable.

Transport/Additional information: Avoid direct sunlight. Make sure of no damage, corrosion, leaks

on the receptacles.

Take necessary measures for preventing cargo shift.

UN "Model Regulation": Not applicable

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

No further relevant information available.

Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

Hazard pictograms Not applicable

Signal word Not applicable

Hazard statements

H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

P273 Avoid release to the environment.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

Seveso category E2 Hazardous to the Aquatic Environment

DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II

None of the ingredients is listed.

National regulations No further information available.

15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

The product is for the industrial use only. We do not guarantee the safety in case the product is used for the other purposes. When using the product for health-care application or food/feed application, consult us in advance.

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Department issuing SDS: EHS Department

Contact: http://www.daikin.com/

Version number of previous version: 5

Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)

ICAO: International Civil Aviation Organisation

ICAO-TI: Technical Instructions by the "International Civil Aviation Organisation" (ICAO)

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Acute Tox. 4: Acute toxicity – Category 4

Acute Tox. 2: Acute toxicity - Category 2

Acute Tox. 3: Acute toxicity – Category 3

Skin Corr. 1C: Skin corrosion/irritation - Category 1C

Eye Dam. 1: Serious eye damage/eye irritation - Category 1

Skin Sens. 1A: Skin sensitisation – Category 1A

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard - Category 1

Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard - Category 1

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard - Category 3

* Data compared to the previous version altered.