

Fluoropolymer NEOFLON EFEP RP-5000

 TECHNICAL
DATASHEET

NEOFLON EFEP RP5000 is a fluoropolymer that has chemical resistance and the capability to adhere to the other materials. It has a good chemical resistance as ETFE at the same time.

Introduction

- NEOFLON EFEP RP-5000 which owns **low melting point** is a copolymer of ETFE and additional third monomer.
- Due to its low melting point, a laminated product such as a multi-layer tube and film with EVOH can be obtained by **co-extrusion molding**.
- **Hot melt adhesion to the other plastics** such as Polyamide with its reactive group.
- **Excellent process ability** and the good chemical resistance as ETFE.
- It can be melt-molded as a thermoplastic resin by **extrusion molding, injection molding, compression molding** and the like.

General physical properties

Item	Unit	Value	Test Method
MFR	g/10min	25	ASTM D 7472 Compliant
Melting Point	°C	195	ASTM D 7472 Compliant
Specific Gravity	-	1.75	ASTM D 7472 Compliant
Tensile Strength	MPa	40	ASTM D 7472 Compliant
Elongation	%	460	ASTM D 7472 Compliant
Tensile Modulus	MPa	700	ASTM D 7472 Compliant

* The above values are representative values, not guaranteed values.

Handling method / Safety information

- Be sure to read the notes on SDS and labels before use.
- This product is intended for general industry, and therefore its adequacy and safety as a raw material for medical purposes cannot be guaranteed.

Packing specification

- 25Kg

For more information, visit our website.

DAIKIN INDUSTRIES, LTD.

<https://www.daikinchemicals.com/>

tds-rp-5000-E_ver02_May_2019

Copyright (C) DAIKIN INDUSTRIES, LTD., 2018