

# Fluoropolymer POLYFLON PTFE D-210C

 TECHNICAL  
DATASHEET

**POLYFLON PTFE D-210C is an opalescent water liquid in which PTFE fine particles are dispersed. It is suitable for a wide range of applications such as glass cloth impregnation, battery binder and additives for drip prevention.**

## Introduction

- POLYFLON PTFE D-210C is a milky white aqueous dispersion with polytetrafluoroethylene polymer particles stabilized with nonionic surfactant without PFOA.
- It is suitable for applications which require **a filler** to a dispersion like **binder of batteries**.
- It adopts more environmentally friendly surfactant than conventional ones.

## General physical properties

Items	Unit	Numeric Value	Test Method
Solid Content	mass%	60	ASTM D 4441
Specific Gravity @25°C	-	1.52	ASTM D 4441
Surfactant Content	mass%/P	6.0	ASTM D 4441
Average Particle Size	μm	0.25	Internal Method
pH @25°C	-	9.7	JIS K 6893
Viscosity @25°C	cP	26	JIS K 6893

\* The above numeric values are representative and not guaranteed.

## Handling method/Safety information

- Be sure to read the notes on SDS and labels before use.
- This product is intended for general industry, and therefore its adequacy and safety as a raw material for medical purposes cannot be guaranteed.

## Packing specification

- 1.5kg, 15 kg, 75kg, 1,000kg

For more information, visit our website.

**DAIKIN INDUSTRIES, LTD.**

<https://www.daikinchemicals.com/>

tds-d-210c-E\_ver03\_Apr\_2021  
Copyright (C) DAIKIN INDUSTRIES, LTD., 2021