

Fluoropolymer NEW POLYFLON PTFE M-111

 TECHNICAL
DATASHEET

NEW POLYFLON PTFE M-111 is a fluoro resin suitable for packing and gaskets that require creep and resistance.

Introduction

- NEW POLYFLON PTFE M-111 is a polytetrafluoroethylene virgin granular fine cut resin.
- Compressing the powder and sintering are a general method for use due to its high melt viscosity.
- **A smooth surface** can be obtained on molded products.
- It is suitable for **packing** and **gasket molding** which require **creep resistance**.

General physical properties

Items	Unit	Numeric Value	Test Method
Average Particle Size	μm	32	Laser diffractometry
Bulk Density	g/mL	0.29	JIS K 6891
Standard Specific Gravity	-	2.17	ASTM D 4894
Tensile Strength	MPa	54	JIS K 6891
Elongation	%	500	JIS K 6891
Shrinkage	%	3.7	Internal Method (50Φ × 50h)
Melt Peak Temperature (Initial)	°C	341	DSC
Melt Peak Temperature (Second)	°C	324	DSC

*The above numeric values are representative and not guaranteed.

Handling method/Safety information

- Be sure to read the notes on SDS and labels before use.
- This product is intended for general industry, and therefore its adequacy and safety as a raw material for medical purposes cannot be guaranteed.

Packing specification

- 25Kg

For more information, visit our website.

DAIKIN INDUSTRIES, LTD.

<https://www.daikinchemicals.com/>