

Polymer additive POLYFLON PTFE L-5

 TECHNICAL
DATASHEET

A fluoropolymer additive with lubricity and wear resistance.
It is suitable especially for grease, paint, and ink.

Introduction

- A low molecular weight polytetrafluoroethylene.
- **Solid lubricant** adding **lubricity** and **wear resistance** to the object.
- Suitable especially for **grease**, **paint** and **ink**.

General physical properties

Item	Unit	Number	Method
Average Particle Size	μm	5 ~ 7	Dry Laser
Bulk Density	g/l	300 ~ 500	ASTM D 4895
Melting Point	°C	326 ~ 328	ASTM D 4895
Specific Surface Area	m ² /g	10 ~ 13	BET
Appearance	—	White powder	Visual

* The above numeric values are representative and not guaranteed.

Handling method/Safety information

- Be sure to read the notes on SDS and labels before use.
- This product is intended for general industry, and therefore its adequacy and safety as a raw material for medical purposes cannot be guaranteed.

Packing specification

- 20kg

For more information, visit our website.

DAIKIN INDUSTRIES, LTD.

<https://www.daikinchemicals.com/>

tds-L-5-E_ver01_Mar_2018.
Copyright (C) DAIKIN INDUSTRIES, LTD., 2018