

Polymer additive **LDW-410**

TECHNICAL DATASHEET

LDW-410 is an opalescent liquid in which the fine particles of low molecular weight PTFE are dispersed. It can be used for additives of imparting water repellency, lubricity etc.

Introduction

- LDW-410 is a milky white aqueous dispersion of polytetrafluoroethylene polymer particles stabilized with nonionic surfactant without PFOA.
- It is suitable for additives to impart water repellency and lubricity.

General physical properties

Items	Unit	Numeric Value	Test method
Solid Content	mass%	40	ASTM D 4441
Specific Gravity @25℃	-	1.3	ASTM D 4441
Surfactant Content	mass%/P	5.6	ASTM D 4441
Average Particle Size	μm	0.20	Internal Method
pH @25℃	-	8.8	JIS K 6893
Viscosity @25℃	cР	6	ASTM D 4441

^{*} The above numeric values are representative and not guaranteed.

Handling method/Safety information

- Be sure to read the notes on SDS and labels before use.
- This product is intended for general industry, and therefore its adequacy and safety as a raw material for medical purposes cannot be guaranteed.

Packing specification

- 1L, 10L, 1m³

For more information, visit our website.

DAIKIN INDUSTRIES.LTD.

https://www.daikinchemicals.com/

tds-ldw-410-E_ver01_Mar_2018 Copyright (C) DAIKIN INDUSTRIES, LTD., 2018